



CryoSat Monthly Quality Report #114

29th January 2020 - 27th February 2020

Author(s): CryoSat Quality Control Team (Telespazio VEGA UK)



AMENDMENT RECORD SHEET

The Amendment Record Sheet below records the history and issue status of this document.

ISSUE	DATE	REASON
1.0	9 April 2020	First issue of report

TABLE OF CONTENTS

- 1. INTRODUCTION 3**
- 1.1 Purpose and Scope 3
- 1.2 Definition of Terms 3
- 2. EXECUTIVE SUMMARY 4**
- 3. INSTRUMENT HEALTH 5**
- 3.1 SIRAL Loss of Surface Track 5
- 3.2 Instrument and Data Availability 6
 - 3.2.1 Recorded Periods of Instrument Unavailability 6
 - 3.2.2 L1 & L2 Offline Data Availability 6
- 4. OFFLINE DATA QUALITY STATUS 8**
- 4.1 Offline Data Quality Overview 8
- 4.2 SIRAL Mode 9
 - 4.2.1 SIRAL Mode Map 9
- 4.3 Attitude Parameters 10
 - 4.3.1 L1B Roll, Pitch and Yaw 10
- 4.4 SIRAL Measured Product Parameters 11
 - 4.4.1 Freeboard 11
 - 4.4.2 Sea Surface Height Anomaly 13
- 4.5 Retracker Failure Analysis 14
- 4.6 Orbit Crossover Derived Parameters 17
 - 4.6.1 Crossover Elevation Statistics and Time Series 17
 - 4.6.2 Crossover Elevation Maps 20
- 4.7 L2 Quality Flags 22
- 4.8 External Auxiliary Corrections 23
 - 4.8.1 Dry Tropospheric Correction 23
 - 4.8.2 Wet Tropospheric Correction 24
 - 4.8.3 Inverse Barometric Correction 25
 - 4.8.4 Dynamic Atmospheric Correction 27
- 5. ANOMALY REPORTS AND PRODUCT QUALITY DISCLAIMERS 29**



1. INTRODUCTION

1.1 Purpose and Scope

This CryoSat Quality Report is distributed by the QA4EO team to keep the CryoSat community informed of the overall mission performance, the status of the SIRAL instrument as well as the data quality of the *CryoSat Ice Products*.

Complementary analysis of the CryoSat Ocean Products is performed by the National Oceanography Centre in Southampton (NOCS). Cyclic Reports for the Ocean Products are also generated and are made available at the following web address: <https://earth.esa.int/web/sppa/mission-performance/esa-missions/cryosat/quality-control-reports/ocean-product-quality-reports>

The report is based on a 30-day reporting period, which has been defined by the data Quality-Analysis (QA) Team of UCL/MSSL since the mission Transfer to Operations (TTO), as part of their routine QA monitoring activity. This 30-day cycle has been defined purely for the purpose of statistic reporting and does not correspond to an official 30-day sub cycle. The actual repeat cycle for CryoSat is 369 days, which consists of 5344 orbits.

This document reports on Offline Ice data (LRM, SAR and SARIn). This document is also available online at the following web address: <http://earth.eo.esa.int/missions/cryosat/reports/cyclic/>

Further product parameter time series, on both a cyclic and weekly basis, are available on the MSSL Quality Monitoring website: <http://cryosat.mssl.ucl.ac.uk/qa/mode.php>

1.2 Definition of Terms

The following terms have been used in this report with the meanings shown.

Term	Definition
QA4EO	Quality Assurance for Earth Observation, reporting to the ESA Data Quality and Algorithms Management Office (EOP-GMQ). This is a consortium responsible for quality of data provided to users including the data calibration and validation, the data processing algorithms, and the routine instrument and processing chain performances.
QA4EO team	In this document, the “QA4EO team” refers to the QA4EO CryoSat team, which can be reached via the following email address: cryosat@eo-sppa.org .
ADF	Auxiliary Data File which is needed by the CryoSat processors to process Level 0 or Level 1B data to higher level products.



2. EXECUTIVE SUMMARY

Cycle Number	114
Cycle Start Date	29th January 2020
Cycle End Date	27th February 2020
Instrument Status	NOMINAL
Data Quality Status	NOMINAL
Processor Updates	None
ADF Updates	None

The health of the SIRAL instrument was found to be nominal during cycle #114.

There was a single period of data unavailability due to a planned orbit manoeuvre. In addition, there were two periods of unplanned data unavailability, both due to a Platform Anomaly. Further information on data unavailability during the reporting period can be found in Section 3.2.1.

There were no changes to Processor Configurations or any Auxiliary Data File updates during the reporting period.

The data quality of Level 1B (L1B) and Level 2 (L2) data products was found to be nominal throughout this reporting period.

3. INSTRUMENT HEALTH

SIRAL parameters are extracted from the Level 0 Data Products and monitored on a daily basis in order to check the health and status of the SIRAL instrument.

3.1 SIRAL Loss of Surface Track

It is expected that the SIRAL altimeter can lose track of the surface over land areas, and this is a nominal feature of the instrument. However, this surface tracking is monitored to ensure there is no loss of track over large areas of ocean as this could indicate a potential issue with the SIRAL instrument.

Figure 1 and Figure 2 show global and polar plots from February 2020, presenting areas where the instrument has lost track of the surface, for each SIRAL mode.

During this reporting period, the loss of SIRAL track was **nominal** for all three SIRAL modes




Figure 1 - Global plot showing areas of loss of track in all SIRAL modes L0 data during February 2020.






Figure 2 - Polar plots showing areas of loss of track in all SIRAL modes L0 data during February 2020.



3.2 Instrument and Data Availability

3.2.1 Recorded Periods of Instrument Unavailability

The following unavailability periods have been noted for SIRAL during this reporting period:

Table 3-1 - SIRAL unavailability periods for Cycle #114

UTC Start	UTC Stop	Reason	Planned	Mode
2020-02-27 15:33:44	2020-02-27 17:24:27	Orbit Manoeuvre	Planned	All
2020-02-21 08:17:00	2020-02-21 08:41:01	Platform Anomaly	Unplanned	All
2020-02-12 09:17:05	2020-02-12 09:53:54	Platform Anomaly	Unplanned	All

During the reporting period there was one planned orbit manoeuvre on the 27th February from 15:33:44 to 17:24:27, during which the SIRAL instrument was unavailable.

There were two unplanned Platform Anomaly unavailability periods. Both were to avoid losing the storage capabilities on the packet stores by using the procedure CMMF_300. Due to the MMFU recovery, SIRAL was successfully restarted.

3.2.2 L1 & L2 Offline Data Availability

During this reporting period there were several additional periods of Offline data unavailability, which cannot be associated to known periods of SIRAL unavailability already provided in Table 3-1.



Table 3-2 - SIRAL data gaps due to working directory failures.

Affected Products	Reason
1 GDR data gap due to product anomaly on 29/01/2020	A working directory failure has caused the product in question not to be produced. This anomaly is known and will be corrected in a future update.
1 GDR data gap due to product anomaly on 31/01/2020	A working directory failure has caused the product in question not to be produced. This anomaly is known and will be corrected in a future update.
1 GDR data gap due to product anomaly on 02/02/2020	A working directory failure has caused the product in question not to be produced. This anomaly is known and will be corrected in a future update.
1 GDR data gap due to product anomaly on 12/02/2020	An anomaly has caused the product(s) in question not to be produced. This anomaly is known and will be corrected in a future update.
1 GDR data gap due to product anomaly on 14/02/2020	An anomaly has caused the product(s) in question not to be produced. This anomaly is known and will be corrected in a future update.
1 GDR data gap due to product anomaly on 24/02/2020	An anomaly has caused the product(s) in question not to be produced. This anomaly is known and will be corrected in a future update.

Processing anomalies are responsible for a small percentage of data product gaps within the offline GDR mode. Currently, two unique anomalies are responsible for data gaps in GDR mode, both will be corrected in a future processing updates. For further information please see the CryoSat Ice Data Quality Status documentation, available to download from <https://earth.esa.int/web/guest/missions/cryosat/product-status>.

Users can be assured that these anomalies explain any noticeable gaps in GDR production. Individual Level 2 Ice products remain available for periods of GDR unavailabilities and do not contain any degradation in quality from the anomalies stated.



4. OFFLINE DATA QUALITY STATUS

4.1 Offline Data Quality Overview

The overall quality of Offline data processed during this reporting period is **nominal**.

During cycle #114, a number of CryoSat Offline products may have been affected by instrument and/or processing issues, which have had a detrimental effect on the data quality of some of the data records within the product. For a full list of the products affected on a particular day please see the relevant Daily Performance Report, available to download from <https://earth.esa.int/web/guest/missions/esa-operational-eo-missions/cryosat/daily-performance-reports>.

Table 4-1 - CryoSat products affected by instrument and/or processing issues during cycle #114

Affected Products	Reason
1 product with warnings on 04/02/2020	The Cal1 correction missing flag is set in a product for 1 or more records.
1 product with warnings on 06/02/2020	The Cal1 correction missing flag is set in a product for 1 or more records.
1 product with warnings on 12/02/2020	The Cal1 correction missing flag is set in a product for 1 or more records.
2 products with warnings on 16/02/2020	The Cal1 correction missing flag is set in a product for 1 or more records.
1 product with warnings on 18/02/2020	The Cal1 correction missing flag is set in a product for 1 or more records.

The Cal1 Correction Missing Flag is set by the L1B processor during the processing of the data. It is an automated check by the processor and the flag is set when any record in a product did not receive any Cal1 corrections.

Users are advised to take note if their product is affected by this error, however this flag may only affect one or a few records so this does not necessarily mean the data product cannot be utilised.

4.2 SIRAL Mode

CryoSat is designed to acquire continuously whilst switching automatically between its three nominal measurement modes, LRM, SAR and SARIn, according to a Geographical Mode Mask. The mask is the basis of the CryoSat mission planning and defines the mode switching of the SIRAL instrument while the satellite revolves around the Earth. The latest operational mask can be viewed on the CryoSat Webpage; <https://earth.esa.int/web/guest/-/geographical-mode-mask-7107>

4.2.1 SIRAL Mode Map

Figure 3 shows global and polar plots of the SIRAL Modes acquired during cycle #114. These plots are generated from offline L2 Geophysical Data Record (GDR) data, which includes a SIRAL mode indicator for each 20 Hz record (field #2). The region in grey is a defined calibration zone where SIRAL is commanded in Calibration (CCAL1) mode each time CryoSat overflies.




Figure 3 - Global and Polar plots of SIRAL Modes for cycle #114.

4.3 Attitude Parameters

4.3.1 L1B Roll, Pitch and Yaw

Figure 4 shows the Spacecraft Attitude Parameters; Roll (field #15), Yaw (field #16) and Pitch (field #17), extracted from L1B products during cycle #114.




Figure 4 – Roll (top), Pitch (middle) and Yaw (bottom) values for L1B Products during cycle #114.

Figure 4 also shows that there is one occurrence where the pitch has an anomalous spike on 16/02/2020 around 03:15. Figure 5 below shows in more detail the plots of pitch vs Time. These plots have been extracted from L1B products on the days when Attribute Parameters are incomplete.

Investigation confirmed that on this day there were some star tracker processing errors at 03:17:00 affecting STR2. The star tracker priority sequence for this period was 2-1-3, therefore STR2 was the preferred choice. In the absence of STR2 data the STR_ATTREF processor would select the next best alternative, however on this occasion unfortunately both STR1 and STR3 were experiencing moon blinding causing the data to be very noisy. As a result there was no good quality data to substitute for STR2 and some unusual values remain.




Figure 5 - Parameter spike due to lack of good quality data.

4.4 SIRAL Measured Product Parameters

4.4.1 Freeboard

CryoSat L2 data includes a SAR mode computed Sea Ice Freeboard calculation (Field #43) for each 20 Hz record, discriminated as 'Sea Ice' by the SAR discriminator flag. Freeboard is defined as the difference in height between sea ice and adjacent water and is used for the calculation of sea ice thickness.

Freeboard values can be negative if there is heavy snow load on thin ice and are calculated using UCL04 model values for snow depth and density.

Figure 6 and Figure 7 show the associated histograms and polar plots of 10km gridded freeboard values from L2 SAR products from cycle #114.




Figure 6 – Histogram of Freeboard for Arctic (above) and Antarctic (below) for cycle #114

During the reporting period, there were no unexpected Quality Flags or errors associated with the computation of the Freeboard values in L2 SAR products.




Figure 7 - Polar plots of 10km Gridded Freeboard values from L2 SAR products in cycle #114.

4.4.2 Sea Surface Height Anomaly

CryoSat L2 data provides the Interpolated Sea Surface Height Anomaly (SSHA) (field #44) for each 20Hz measurement record. The SSHA value is used to compute the Freeboard in the sea-ice processing within the SAR chain; therefore it is not currently output for LRM or SARIn mode.

Figure 8 shows polar plots of the SIRAL SSHA values from L2 products during cycle #114. The values in red indicate areas where SSHA is not provided in SAR mode, over land areas.




Figure 8 –Polar plots of SSHA for cycle #114.

The values for this reporting period are all within the expected range and no issues are highlighted for this reporting period.



4.5 Retracker Failure Analysis

The table below summarises the retrackerers currently used for the CryoSat Baseline-C processing:

Table 4-2 - Current CryoSat Retrackerers in Baseline-C

Retracker ID	LRM	SAR	SARIn
1	Ocean CFI Model Fit	Laxon/Ridout Sea Ice Model Fit	Wingham/Wallis Model Fit
2	UCL Land-Ice (LIRT)		
3	OCOG		

CryoSat L2I products include a Retracker Failure Flag for each 20Hz measurement record (field #75, bits 20, 21, 22) which indicates the overall success or failure of the retracker algorithm for that measurement waveform.

Table 4-3 shows the statistics of retracker failures for this reporting period, cycle #114.

Table 4-3 - Statistics of Global Retracker Failures for Cycle #114

LRM CFI Failed	LRM LIRT Failed	LRM OCOG Failed	SAR Failed	SARIn Failed
16.46%	12.53%	4.79%	1.89%	7.03%

Figure 9 shows the global retracker failure time series for each of the CryoSat retrackerers, from L2I products since the beginning of the mission.




Figure 9 – Time Series for Retracker Failure Flags

Figure 10 compares the occurrence of the L2 LRM Retracker Failure Flag (field #75, bits 20,21,22) for each of the LRM Retracker for cycle #114.




Figure 10 – Global plots showing Retracker Failure Flags for LRM mode for cycle #114:
LRM CFI (top), LRM LIRT (middle), LRM OCOG (bottom)

Figure 10 shows that the main difference between the failure rates of each of the LRM retrackerers is due mainly to failures over land areas for which the OCOG retracker has the least number of failures, followed by the LIRT and then the CFI retracker, which has the most failures over land areas. **This is currently in line with the expected performance of the current LRM retrackerers.**

Figure 11 and Figure 12 show the occurrence of the L2 SAR and SARIn Retracker Failure Flags (field #75, bit 20) for cycle #114.




Figure 11 – Global plots showing Retracker Failure Flags for SAR mode for cycle #114




Figure 12 – Global plots showing Retracker Failure Flags for SARIn mode for cycle #114

The retracker failure flags shown above are currently in line with the expected performance of the current SAR and SARIn retrackers.

4.6 Orbit Crossover Derived Parameters

This section provides results from crossover processing of offline L2 data from cycle #114.

The crossover elevations presented in the sections below are calculated by interpolating pairs of slope corrected elevation measurements of ascending and descending arcs to the crossover point and calculating the difference.

It should be noted that the DEM is not removed for this analysis and as L2 data is used in input, the crossover elevations are calculated using the range corrected L2 elevation values. The use of the retracker in the elevation calculation depends on the SIRAL mode; please refer to Table 4-2.

4.6.1 Crossover Elevation Statistics and Time Series

Table 4-4 below provides r.m.s elevation difference and the mean difference at crossover, in different modes and areas, from the crossovers generated from L2 data from cycle #114.



Table 4-4 - Statistics of surface elevation crossover processing for LRM and SARIn data for cycle #114

Location	Statistic	LRM	SARIn
Antarctica (Land)	r.m.s (m)	0.41 m	1.80 m
	Mean Difference (m)	0.01 m	-0.01 m
	% of xovers < 10.0m	63.2%	84.8%
Greenland (Land)	r.m.s (m)	0.30 m	1.89 m
	Mean Difference (m)	-0.01 m	0.02 m
	% of xovers < 1.0m	77.3 %	73.3 %
Global Oceans	r.m.s (m)	0.145 m	
	Mean Difference (m)	0.00 m	
	% of xovers < 1.0m	98.9 %	

Figure 13 shows the time series for crossover r.m.s values of surface elevation from CryoSat products since the beginning of the mission for LRM and SARIn modes over Antarctica, Greenland and Global Oceans.

Figure 14 shows the time series of Mean Difference in elevation values at crossovers from CryoSat products since the beginning of the mission for LRM and SARIn modes over Antarctica, Greenland and Global Oceans.




Figure 13 - Time series for crossover elevation r.m.s values from beginning of the mission




Figure 14 - Time series for Mean Difference in elevation at crossovers from beginning of the mission

The mean difference in elevation values at crossovers is expected to be as close to zero as possible. Although Figure 14 shows the values of mean difference to be fluctuating since the beginning of the mission, the mean difference values all remain within the expected range.

In SARIn mode, over Antarctica and especially over Greenland, there is a higher fluctuation in the mean difference; a higher standard deviation would be expected in SARIn mode due to the smaller footprint – it is more likely that a slightly different part of the surface is being observed at the crossover point.

In addition, for SARIn mode the footprint is also different for ascending and descending tracks. On the other hand the larger LRM footprint has a smoothing effect and is not dependent on track direction.

4.6.2 Crossover Elevation Maps

Figure 15 and Figure 16 show spatial polar maps of elevation differences calculated at crossover per 10 km² grid cells for L2 products from cycle #111




Figure 15 - Greenland and Antarctica maps of LRM elevation differences for cycle #114.




Figure 16 - Greenland and Antarctica maps of SARIn elevation differences for cycle #114

Figure 15 shows an unusual pattern in the ice sheet's elevation near central Antarctica. This static pattern is an artefact arising from the interaction of the polarisation of CryoSat's antenna with the structure of the ice surface induced by wind. Further details can be found at the following webpage: [http://www.esa.int/Our Activities/Observing the Earth/CryoSat/CryoSat detects hidden Antarctic pattern](http://www.esa.int/Our_Activities/Observing_the_Earth/CryoSat/CryoSat_detects_hidden_Antarctic_pattern)

Since the pattern is static, it can be removed by users applying an elevation correction (see Armitage *et al.*, 2013, "Meteorological Origin of the Static Crossover Pattern Present in Low-Resolution-Mode CryoSat-2 Data over Central Antarctica"). However, this elevation correction is not currently applied in the CryoSat processing and is therefore not applied in the spatial polar maps above.



4.7 L2 Quality Flags

The CryoSat offline L2 data products include a Quality Flag word (field #50) for each 20 Hz measurement record. The bit values of this flag indicate an assessment of the measurement quality by the CryoSat processing chains.

The table below provides the statistics of the main Quality Flags during this reporting period, which can be used to indicate a data quality issue. CryoSat data users should ensure the Quality Flags are checked in the CryoSat data products they are using. In some cases data records which have a Quality Flag set should be discarded by the user prior to any data analysis.

Table 3-1 shows the Quality Flags which were flagged over each surface area during this reporting period; **during cycle #114 there has been no unexpected Quality Flags set in the CryoSat L2 products.**

Table 4-5 - Percentage of Quality Flags set in L2 products during Cycle #114

Quality Flag	LRM Ice	LRM Land	LRM Ocean	SARIn Ice	SARIn Land	SAR Ocean
Height Error	16.3 %	73.59 %	0.27 %	8.55 %	18.45 %	1.21 %
Backscatter Error	16.07 %	72.9 %	0.27 %	8.51 %	18.3 %	1.21 %

The large number of “Height Error” and “Backscatter Error” Quality Flags, especially over Land and Land Ice, are due to the failure of the altimeter to track the surface over rough surface terrain – this is expected behaviour of the altimeter.

From looking at the plots provided in Section 4.5, it is clear the presence of the Quality Flags shown in Table 4-5 coincide with the failure of the Retracker in both LRM and SARIn modes.

All users are advised to manually review the quality of the waveforms within their products by looking at the Quality Flags and rejecting any waveforms which have the Height/Backscatter Error Flags set.



4.8 External Auxiliary Corrections

Surface Height measurements, which are provided in offline L2 products, are corrected for atmospheric propagation delays and geophysical surface variations.

Table 4-6 provides the r.m.s value and availability of each external correction in the L2 products for cycle #114.

Table 4-6 – r,m.s value and availability of each external auxiliary correction in the L2 products for cycle #114

	Dry Tropospheric Correction	Wet Tropospheric Correction	Inverse Barometric Correction	Dynamic Atmospheric Correction
Availability (%)	100%	100%	100%	100%
r.m.s value (mm)	2225.99	164.394	175.614	131.472

During this reporting period there were no issues with the availability of auxiliary corrections in the processing of CryoSat products.

The following sections provide global and polar maps of the value of each correction for cycle #114. Furthermore, the global trend from each 30-day cycle, since the beginning of the mission is also provided.

4.8.1 Dry Tropospheric Correction

The Dry Tropospheric Correction is the correction for refraction due to the dry gas component of the atmosphere, which generates a path delay in the radar return signal. For CryoSat, this correction is not received via a direct ADF input, but is computed by the CryoSat processors using dynamic mean surface pressure ECMWF Meteo grids. Figure 17 shows, geographically, the Dry Tropospheric Correction values, applied to the L2 data during cycle #114 and Figure 18 shows the trends in r.m.s values since the beginning of the mission.

Global Dry Tropospheric Correction Values for Data Take 114 : 29/01/2020 – 27/02/2020 Baseline-D




Figure 17 - Global plot of Dry Tropospheric Correction for cycle #114




Figure 18 - Dry Tropospheric Correction RMS value trend from beginning of mission

4.8.2 Wet Tropospheric Correction

The Wet Troposphere Correction is the correction for the path delay in the radar return signal due to liquid water in the atmosphere. Unlike the Dry Tropospheric Correction, the Wet Tropospheric Correction is retrieved as a direct input from ECMWF analysed grids, and is then formatted to the CryoSat PDS file standard before being used by the processor. Figure 19 shows, geographically, the

Wet Tropospheric Correction values, applied to the L2 data during cycle #114 and Figure 20 shows the trends in r.m.s values since the beginning of the mission.




Figure 19 - Global plot of Wet Tropospheric Correction for cycle #114




Figure 20 – Wet Tropospheric Correction RMS value trend from beginning of mission

4.8.3 Inverse Barometric Correction

The Inverse Barometric Correction compensates for variations in sea surface height due to atmospheric pressure variations (atmospheric loading). For CryoSat this is calculated using dynamic

surface pressure based on ECMWF outputs. The correction is only used in SAR mode over sea ice and when the surface type is “Open Ocean”. Figure 21 shows, geographically, the value of the Inverse Barometric Correction, applied to the L2 data during cycle #114 and Figure 22 shows the trends in r.m.s values since the beginning of the mission.




Figure 21 - Global plot of Inverse Barometric Correction for cycle #114




Figure 22 – Inverse Barometric Correction RMS value trend from beginning of mission

4.8.4 Dynamic Atmospheric Correction

The Dynamic Atmospheric Correction (DAC) is needed to correct for the depression of the ocean surface caused by the local barometric pressure and wind effects. This is provided by Meteo grids and is a combination of the high frequency, high resolution 2D Gravity Waves Model (MOG2D), an ECMWF ocean model, and the low frequency Inverse Barometric (IB) Correction. The correction is used over ocean only where there is no sea-ice cover, i.e. for LRM and in a few cases for SARIn mode when the surface type is "Open Ocean".

Figure 23 shows, geographically, the DAC values, applied to the L2 data during cycle #114 and Figure 24 shows the trends in r.m.s values since the beginning of the mission.




Figure 23 - Global plot of Dynamic Atmospheric Correction for cycle #114




Figure 24 – Dynamic Atmospheric Correction RMS value trend from beginning of mission



5. ANOMALY REPORTS AND PRODUCT QUALITY DISCLAIMERS

An updated list of *all known anomalies* which have been opened and tracked on the IPF and affect the quality of the distributed data products, is provided at the link below:

<https://earth.esa.int/web/guest/missions/cryosat/product-status>