





3. Instrument Configuration

The SIRAL instrument configuration for the day of acquisition is provided below.

| SIRAL instrument(s) in use: | SIRAL - A | |
|-----------------------------|----------------|--|
| Star Tracker(s) in use: | Star Tracker 1 | |

4. Level 1B Calibration Data Quality Check

4.1 L1 CAL Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a binary product file (.DBL).

Number of products with errors:

4.2 L1 CAL Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the processing chain.

0

| 4.3 L1 CAL Auxiliary Data File Usage Check | | |
|--|---|--|
| Each product is checked for missing Data Set Descriptors wrt a pre-determined ba | seline and also to check the validity of Auxi | liary Data Files is correct. |
| Number of products with errors: 0 | · · · · · · · · · · · · · · · · · · · | |
| 4.4 L1 CAL Measurement Confidence Flags | | |
| | 1) for each measurement record. The bit u | un af this flag indicates any making so when ast |
| CryoSat Cal1 and Cal2 data includes a measurement confidence flag word (field 1 Number of products with errors: 0 | 1) for each measurement record. The bit va | aue of this flag indicates any problems when set. |
| | D FDM Data Quality Cha | alı |
| | B FDM Data Quality Che | CK |
| 5.1 L1B FDM Product Format Check | | |
| Each product, retrieved and unpacked from the science server, is checked to ensu Number of products with errors: 0 | re it consists of both an XML header file (.H | IDR) and a binary product file (.DBL). |
| 5.2 L1B FDM Product Header Analysis | | |
| For all products, a series of pre-defined checks are carried out on the MPH and SF | 2H in order to identify any inconsistencies a | nd/or errors raised by the around-segment processing chain |
| Number of products with errors: 0 | | hard ended by the ground beginent proceeding andin. |
| 5.2 L4D EDM Auxiliany Data File Lloogo Check | | |
| 5.3 L1B FDM Auxilary Data File Usage Check | coline and also to aback the validity of Auvi | linny Data Eilea is correct |
| Each product is checked for missing Data Set Descriptors wrt a pre-determined ba Number of products with errors: 0 | seine and also to check the validity of Auxi | nary Data Files is correct. |
| 5.4 L1B Correction Error Flags | | |
| Each product is checked to detect auxiliary corrections flagged by the ground-stati | on processing chain as missing or containir | ng errors. |
| Number of products with errors: 0 | | |
| 5.5 L1B FDM Measurement Confidence Flags | | |
| CryoSat L1B data includes a measurement confidence flag word (field 14) for each | measurement record. The bit value of this | flag indicates any problems when set |
| Number of products with errors: 4 | | |
| Product | Test Failed | Description |
| CS_OFFL_SIR_FDM_1B_20130531T155618_20130531T155640_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20130531T173235_20130531T173250_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20130531T190908_20130531T191039_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20130531T215841_20130531T223249_B001 | Attitude correction missing | The attitude has not been corrected |
| 6. Level | 2 FDM Data Quality Cheo | - sk |
| 6.1 L2 FDM Product Format Check | | |
| | re it consists of both on VML booder file () | IDD) and a biggrup dust file (DDI) |
| Each product, retrieved and unpacked from the science server, is checked to ensu Number of products with errors: 0 | | |
| | | |
| 6.2 L2 FDM Product Header Analysis | | |
| For all products, a series of pre-defined checks are carried out on the MPH and SF | PH in order to identify any inconsistencies a | nd/or errors raised by the processing chain. |
| Currently there is a high number of processing error flags set within the Level 2 FD field #29) and also within the L2 Product files (MPH field #35 and SPH field #33). T percentage of Data Set Records free of processing errors is below the minimum ac | hey are set by the FDM processor when an | n error is detected during the L2 processing and also when the |
| This issue is under investigation. | | |
| Number of products with errors: 0 | | |
| 6.3 L2 FDM Auxiliary Data File Usage Check | | |
| Each product is checked for missing Data Set Descriptors wrt a pre-determined ba | seline and also to check the validity of Auxi | liary Data Files is correct. |
| Number of products with errors: 0 | | |
| 6.4 L2 FDM Correction Error Flags | | |
| Each product is checked to detect auxiliary corrections flagged by the ground-stati | on processing chain as missing or containir | ig errors. |
| Number of products with errors: 0 | | |

6.5 L2 FDM Measurement Confidence Flags

CryoSat L2 data includes a quality flag word (field 8) for each 20-Hz measurement record. The bit value of this flag is an assessment of the measurement quality by the processing chain.

Number of products with errors:

| Product | Test Failed | Description |
|---|-----------------------------|-------------------------------------|
| CS_OFFL_SIR_FDM_220130531T155618_20130531T155640_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220130531T173235_20130531T173250_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220130531T190908_20130531T191039_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220130531T215841_20130531T223249_B001 | Attitude correction missing | The attitude has not been corrected |

6.6 L2 FDM Range Measurement Flags

Each product is checked to detect range measurements flagged by the processing chain as missing or containing errors. 2

4

Number of products with errors:

| Product | Test Failed | Description |
|---|---------------------------|--|
| CS_OFFL_SIR_FDM_220130531T102337_20130531T104839_B001 | OCOG Retracked Range Flag | The master fail flag is set by the OCOG call, for one or more records, indicating the values stored in fields #18, #19, #20 and #21 should be ignored for these records. |
| CS_OFFL_SIR_FDM_220130531T143457_20130531T144208_B001 | OCOG Retracked Range Flag | The master fail flag is set by the OCOG call, for one or more records, indicating the values stored in fields #18, #19, #20 and #21 should be ignored for these records. |

6.7 L2 FDM SWH and Backscatter Measurement Flags

Each product is checked to detect parameters related to SWH and sigma0 that are flagged by the processing chain as missing or containing errors.

Number of products with errors:

6.8 L2 FDM Geophysical Measurement Flags

Each product is checked to detect geophysical measurements flagged by the processing chain as missing or containing errors. 6

0

2

0

Number of products with errors:

| Product | Test Failed | Description |
|---|-------------------------------|--|
| CS_OFFL_SIR_FDM_220130531T004614_20130531T005903_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. |
| CS_OFFL_SIR_FDM_220130531T070440_20130531T073808_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. |
| CS_OFFL_SIR_FDM_220130531T102337_20130531T104839_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. |
| CS_OFFL_SIR_FDM_220130531T143457_20130531T144208_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. |
| CS_OFFL_SIR_FDM_220130531T155640_20130531T155656_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. |
| CS_OFFL_SIR_FDM_220130531T193026_20130531T200408_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. |

7. QCC Check

The QCC is a CryoSat facility that performs a primary survey of data products immediately after production by the PDS and LTA processing facilities. A list of the tests which raised errors or warnings is provided below.

| Product type | Nb. Products | Nb. QCC Reports | Nb. Valid | Nb. Warnings | Nb. Errors |
|--------------|--------------|-----------------|-----------|--------------|------------|
| SIR_FDM_1B | 138 | 137 | 137 | 0 | 0 |
| SIR_FDM_2 | 137 | 136 | 0 | 136 | 0 |

7.1 QCC Errors

Number of QCC reports with errors:

7.2 Missing QCC Reports

Number of products with missing QCC reports:

Product name

CS_OFFL_SIR_FDM_1B_20130530T235644_20130531T001307_B001

CS_OFFL_SIR_FDM_2__20130530T235644_20130531T001307_B001