






## 1. Overview


			Server check: calval-pds.cryosat.esa.int
			Product Software Check
	Report Production Date:	10-Jun-2013	Product Format Check
			Product Header Analysis
	Data Used:	L1 and L2 Fast Delivery Marine Mode (FDM), and CAL Data	Auxiliary Data File Usage
			Correction Error Flags

Check	Status
Server check: science-pds.cryosat.esa.int	Nominal
Server check: calval-pds.cryosat.esa.int	Nominal
Product Software Check	Nominal
Product Format Check	Nominal
Product Header Analysis	Nominal
Auxiliary Data File Usage	See Section 5.3 and 6.3
Correction Error Flags	See Sections 5.4 and 6.4
Measurement Confidence Flags	See Sections 5.5.6.5.6.6.6.7 and 6.8

Mission / Instrument News			
08-Jun-2013	None		
09-Jun-2013	None		
10-Jun-2013	Nothing planned		

# 2. Global Coverage





Global Coverage

## 3. Instrument Configuration

The SIRAL instrument configuration for the day of acquisition is provided below.

SIRAL instrument(s) in use:	SIRAL - A
Star Tracker(s) in use:	Star Tracker 1 & 2

# 4. Level 1B Calibration Data Quality Check

### 4.1 L1 CAL Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a binary product file (.DBL).

Number of products with errors:

0

#### 4.2 L1 CAL Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the processing chain.

#### 4.3 L1 CAL Auxiliary Data File Usage Check

Each product is checked for missing Data Set Descriptors wrt a pre-determined baseline and also to check the validity of Auxiliary Data Files is correct.

Number of products with errors:

1

#### 4.4 L1 CAL Measurement Confidence Flags

CryoSat Cal1 and Cal2 data includes a measurement confidence flag word (field 11) for each measurement record. The bit value of this flag indicates any problems when set.

Number of products with errors:

## 5. Level 1B FDM Data Quality Check

#### 5.1 L1B FDM Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a binary product file (.DBL).

Number of products with errors:

0

#### 5.2 L1B FDM Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the ground-segment processing chain.

Number of products with errors:

Λ

#### 5.3 L1B FDM Auxilary Data File Usage Check

Each product is checked for missing Data Set Descriptors wrt a pre-determined baseline and also to check the validity of Auxiliary Data Files is correct.

Number of products with errors:

Product	AUX File	Comment
All SIR_FDM_1B_ products from 20130609T000000 to 20130609T060000	CS_OPER_AUXISURFPS_20130609T000000_20130609T00000 0_0001 CS_OPER_AUXISURFPS_20130609T060000_20130609T06000 0_0001	Missing Forecast Auxiliary Files:
All SIR_FDM_1B_ products from 20130609T060000 to 20130609T120000	CS_OPER_AUXISURFPS_20130609T060000_20130609T06000 0_0001 CS_OPER_AUXISURFPS_20130609T120000_20130609T12000 0_0001	Missing Forecast Auxiliary Files:
All SIR_FDM_1B_ products from 20130609T120000 to 20130609T180000	CS_OPER_AUXISURFPS_20130609T120000_20130609T12000 0_0001 CS_OPER_AUXISURFPS_20130609T180000_20130609T18000 0_0001	Missing Forecast Auxiliary Files:
All SIR_FDM_1B_ products from 20130609T180000 to 20130610T000000	CS_OPER_AUXISURFPS_20130609T180000_20130609T18000 0_0001 CS_OPER_AUXISURFPS_20130610T000000_20130610T00000 0_0001	Missing Forecast Auxiliary Files:

### 5.4 L1B Correction Error Flags

Each product is checked to detect auxiliary corrections flagged by the ground-station processing chain as missing or containing errors.

Number of products with errors:

All

Product	Test Failed	Description
All SIR_FDM_1B products	tropospheric correction error, Inverse	Due to multiple missing Forecast Auxiliary Files, there was an error with the Dry tropospheric, Wet tropospheric and Inverse barometric corrections

### 5.5 L1B FDM Measurement Confidence Flags

CryoSat L1B data includes a measurement confidence flag word (field 14) for each measurement record. The bit value of this flag indicates any problems when set.

Number of products with errors:

8

Product	Test Failed	Description
CS_OFFL_SIR_FDM_1B_20130609T065048_20130609T070356_B001	Echo error	The Echo Rx1 Error flag is set, indicating a degraded raw echo.
CS_OFFL_SIR_FDM_1B_20130609T162507_20130609T163304_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_1B_20130609T173913_20130609T180104_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_1B_20130609T180106_20130609T181017_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_1B_20130609T181109_20130609T181530_B001	Echo error	The Echo Rx1 Error flag is set, indicating a degraded raw echo.
CS_OFFL_SIR_FDM_1B_20130609T194834_20130609T194926_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_1B_20130609T205844_20130609T213050_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_1B_20130609T231200_20130609T231521_B001	Attitude correction missing	The attitude has not been corrected

### 6. Level 2 FDM Data Quality Check

#### 6.1 L2 FDM Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a binary product file (.DBL)

Number of products with errors:

#### 6.2 L2 FDM Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the processing chain.

Currently there is a high number of processing error flags set within the Level 2 FDM products (Product\_Err and L2\_Proc\_Flag). These flags are set within L2 Header files (MPH field #19 and SPH field #29) and also within the L2 Product files (MPH field #35 and SPH field #33). They are set by the FDM processor when an error is detected during the L2 processing and also when the percentage of Data Set Records free of processing errors is below the minimum acceptable threshold set within the processor (currently set to 5%).

This issue is under investigation.

Number of products with errors:

0

#### 6.3 L2 FDM Auxiliary Data File Usage Check

Each product is checked for missing Data Set Descriptors wrt a pre-determined baseline and also to check the validity of Auxiliary Data Files is correct.

Number of products with errors:

. . . .

Product	AUX File	Comment
All SIR_FDM_2_ products from 20130609T000000 to 20130609T060000	CS_OPER_AUXISURFPS_20130609T000000_20130609T00000 0_0001 CS_OPER_AUXISURFPS_20130609T060000_20130609T06000 0_0001	Missing Forecast Auxiliary Files:
All SIR_FDM_2_ products from 20130609T060000 to 20130609T120000	CS_OPER_AUXISURFPS_20130609T060000_20130609T06000 0_0001 CS_OPER_AUXISURFPS_20130609T120000_20130609T12000 0_0001	Missing Forecast Auxiliary Files:
	CS_OPER_AUXISURFPS_20130609T120000_20130609T12000 0_0001 CS_OPER_AUXISURFPS_20130609T180000_20130609T18000 0_0001	Missing Forecast Auxiliary Files:
	CS_OPER_AUXISURFPS_20130609T180000_20130609T18000 0_0001 CS_OPER_AUXISURFPS_20130610T0000000_20130610T00000 0_0001	Missing Forecast Auxiliary Files:

### 6.4 L2 FDM Correction Error Flags

Each product is checked to detect auxiliary corrections flagged by the ground-station processing chain as missing or containing errors.

ΑII

Number of products with errors:

Product	Test Failed	Description
	tropospheric correction error, Inverse barometric	Due to a missing Forecast Auxiliary File, there was an error with the Dry tropospheric, Wet tropospheric and Inverse barometric corrections

### 6.5 L2 FDM Measurement Confidence Flags

CryoSat L2 data includes a quality flag word (field 8) for each 20-Hz measurement record. The bit value of this flag is an assessment of the measurement quality by the processing chain.

Number of products with errors:

Product	Test Failed	Description
CS_OFFL_SIR_FDM_220130609T065048_20130609T070356_B001	Echo error	The Echo Rx1 Error flag is set, indicating a degraded raw echo.
CS_OFFL_SIR_FDM_220130609T162507_20130609T163304_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_220130609T180106_20130609T181017_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_220130609T181109_20130609T181530_B001	Echo error	The Echo Rx1 Error flag is set, indicating a degraded raw echo.
CS_OFFL_SIR_FDM_220130609T194834_20130609T194926_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_220130609T205844_20130609T213050_B001	Attitude correction missing	The attitude has not been corrected
CS_OFFL_SIR_FDM_220130609T231200_20130609T231521_B001	Attitude correction missing	The attitude has not been corrected

### 6.6 L2 FDM Range Measurement Flags

Each product is checked to detect range measurements flagged by the processing chain as missing or containing errors.

Number of products with errors:

Product	Test Failed	Description
CS_OFFL_SIR_FDM_220130608T232858_20130609T000302_B001	OCOG Retracked Range Flag	The master fail flag is set by the OCOG call, for one or more records, indicating the values stored in fields #18, #19, #20 and #21 should be ignored for these records.
CS_OFFL_SIR_FDM_220130609T070539_20130609T072748_B001	OCOG Retracked Range Flag	The master fail flag is set by the OCOG call, for one or more records, indicating the values stored in fields #18, #19, #20 and #21 should be ignored for these records.
CS_OFFL_SIR_FDM_220130609T115251_20130609T122534_B001	OCOG Retracked Range Flag	The master fail flag is set by the OCOG call, for one or more records, indicating the values stored in fields #18, #19, #20 and #21 should be ignored for these records.
CS_OFFL_SIR_FDM_220130609T165535_20130609T172353_B001	OCOG Retracked Range Flag	The master fail flag is set by the OCOG call, for one or more records, indicating the values stored in fields #18, #19, #20 and #21 should be ignored for these records.

### 6.7 L2 FDM SWH and Backscatter Measurement Flags

Each product is checked to detect parameters related to SWH and sigma0 that are flagged by the processing chain as missing or containing errors.

Number of products with errors:

2

Product	Test Failed	Description
CS_OFFL_SIR_FDM_220130609T200711_20130609T204214_B001		The master fail flag is set by the CFI call, for one or more records, indicating the values stored in fields #47, #48, #49 and #50 should be ignored for these records.
CS_OFFL_SIR_FDM_220130609T214549_20130609T222105_B001		The master fail flag is set by the CFI call, for one or more records, indicating the values stored in fields #47, #48, #49 and #50 should be ignored for these records.

## 6.8 L2 FDM Geophysical Measurement Flags

Each product is checked to detect geophysical measurements flagged by the processing chain as missing or containing errors.

Number of products with errors:

All

Product	Test Failed	Description
All SIR_FDM_2 products	U-Wind component error, V-Wind component error	Due to a missing Forecast Auxiliary File, there was an error with the U-Wind and V-wind components of the ECMWF model wind vector.
CS_OFFL_SIR_FDM_220130608T232858_20130609T000302_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T001524_20130609T005110_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T012651_20130609T013748_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T065048_20130609T070356_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T070539_20130609T072748_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T115251_20130609T122534_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T165535_20130609T172353_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T180106_20130609T181017_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_2_20130609T214549_20130609T222105_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.
CS_OFFL_SIR_FDM_220130609T232415_20130610T000027_B001	Ocean Retracking Quality Flag	The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records.

## 7. QCC Check

The QCC is a CryoSat facility that performs a primary survey of data products immediately after production by the PDS and LTA processing facilities. A list of the tests which raised errors or warnings is provided below.

Product type	Nb. Products	Nb. QCC Reports	Nb. Valid	Nb. Warnings	Nb. Errors
SIR_FDM_1B	68	68	53	15	0
SIR_FDM_2	68	67	0	67	0

## 7.1 QCC Errors

Number of QCC reports with errors:

0

## 7.2 Missing QCC Reports

Number of products with missing QCC reports:

2

#### Product name

CS\_OFFL\_SIR\_FDM\_1B\_20130608T232858\_20130609T000302\_B001

CS\_OFFL\_SIR\_FDM\_2\_\_20130608T232858\_20130609T000302\_B001