



IDEAS+ Daily Report for NRT data:

<u>01/01/2015</u>

| Report Production Date: | 06-Jan-2015 | Check | Status |
|-------------------------|-------------------------------------|---|---|
| Report Production Date. | | Server check: science-pds.cryosat.esa.int | Nominal |
| Data Used: | L1 and L2 Fast Delivery Marine Mode | Server check: calval-pds.cryosat.esa.int | Nominal |
| Data Used: | (FDM), and CAL Data | Product Software Check | Nominal |
| | | Product Format Check | Nominal |
| | | Product Header Analysis | Nominal |
| | | Auxiliary Data File Usage | Nominal |
| | | Correction Error Flags | Nominal |
| | | Measurement Confidence Flags | See Sections 5.5, 6.5, 6.6, 6.7 and 6.8 |

| Mission / Instrument News | | | |
|---------------------------|-----------------|--|--|
| 31-Dec-2014 | None | | |
| 01-Jan-2015 | None | | |
| 02-Jan-2015 | Nothing planned | | |





3. Instrument Configuration

The SIRAL instrument configuration for the day of acquisition is provided below.

| SIRAL instrument(s) in use: | SIRAL - A |
|-----------------------------|----------------|
| Star Tracker(s) in use: | Star Tracker 1 |

4. Level 1B Calibration Data Quality Check

4.1 L1 CAL Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a binary product file (.DBL).

Number of products with errors:

4.2 L1 CAL Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the processing chain.

0

| 4.3 L1 CAL Auxiliary Data File Usage Check | | |
|--|--|--|
| Each product is checked for missing Data Set Descriptors wrt a pre-determined I | baseline and also to check the validity of | of Auxiliary Data Files is correct. |
| Number of products with errors: 0 | | |
| 4.4 L1 CAL Measurement Confidence Flags | | |
| CryoSat Cal1 and Cal2 data includes a measurement confidence flag word (field | 11) for each measurement record. The | e bit value of this flag indicates any problems when set. |
| Number of products with errors: 0 | | |
| 5. Leve | el 1B FDM Data Quality | y Check |
| 5.1 L1B FDM Product Format Check | | |
| Each product, retrieved and unpacked from the science server, is checked to en | sure it consists of both an XML header | file (.HDR) and a binary product file (.DBL). |
| Number of products with errors: 0 | | |
| 5.2 L1B FDM Product Header Analysis | | |
| For all products, a series of pre-defined checks are carried out on the MPH and | SPH in order to identify any inconsister | ncies and/or errors raised by the ground-segment processing chain. |
| Number of products with errors: 0 | | |
| 5.3 L1B FDM Auxilary Data File Usage Check | | |
| Each product is checked for missing Data Set Descriptors wrt a pre-determined I | baseline and also to check the validity | of Auviliary Data Files is correct |
| Number of products with errors: 0 | | |
| | | |
| 5.4 L1B Correction Error Flags | | |
| Each product is checked to detect auxiliary corrections flagged by the ground-sta | ation processing chain as missing or co | intaining errors. |
| Number of products with errors: 0 | | |
| 5.5 L1B FDM Measurement Confidence Flags | | |
| | - hard a second the second the second | |
| CryoSat L1B data includes a measurement confidence flag word (field 14) for ea Number of products with errors: 15 | ch measurement record. The bit value | or this flag indicates any problems when set. |
| | | |
| | Test Failed | Description |
| CS_OFFL_SIR_FDM_1B_20150101T010939_20150101T013209_B001 | Echo error | The Echo Rx1 Error flag is set, indicating a degraded raw echo |
| CS_OFFL_SIR_FDM_1B_20150101T042825_20150101T042947_B001 | Echo error | The Echo Rx1 Error flag is set, indicating a degraded raw echo |
| CS_OFFL_SIR_FDM_1B_20150101T121652_20150101T121706_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T121708_20150101T122234_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T135857_20150101T135955_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T153809_20150101T153914_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T153914_20150101T153929_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T154220_20150101T154459_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T154554_20150101T154559_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T155830_20150101T160748_B001 | Attitude correction missing | The attitude has not been corrected |
| CS OFFL SIR FDM 1B 20150101T161034 20150101T163206 B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T163819_20150101T163942_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_20150101T163950_20150101T164358_B001 | Attitude correction missing | The attitude has not been corrected |
| CS OFFL SIR FDM 1B 20150101T164846 20150101T165906 B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_1B_201501011104540_201501011103500_5001 CS_OFFL_SIR_FDM_1B_201501011170054_201501011171329_8001 | Attitude correction missing | The attitude has not been corrected |
| | | |
| 6. Lev | vel 2 FDM Data Quality | Check |
| | | |

6.1 L2 FDM Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a binary product file (.DBL)

Number of products with errors:

6.2 L2 FDM Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the processing chain.

Currently there is a high number of processing error flags set within the Level 2 FDM products (Product_Err and L2_Proc_Flag). These flags are set within L2 Header files (MPH field #19 and SPH field #29) and also within the L2 Product files (MPH field #35 and SPH field #33). They are set by the FDM processor when an error is detected during the L2 processing and also when the percentage of Data Set Records free of processing errors is below the minimum acceptable threshold set within the processor (currently set to 5%).

This issue is under investigation.

Number of products with errors:

6.3 L2 FDM Auxiliary Data File Usage Check

Each product is checked for missing Data Set Descriptors wrt a pre-determined baseline and also to check the validity of Auxiliary Data Files is correct.

Number of products with errors:

6.4 L2 FDM Correction Error Flags

Each product is checked to detect auxiliary corrections flagged by the ground-station processing chain as missing or containing errors.

0

0

0

6.5 L2 FDM Measurement Confidence Flags

ы.

har of products with a

CryoSat L2 data includes a quality flag word (field 8) for each 20-Hz measurement record. The bit value of this flag is an assessment of the measurement quality by the processing chain.

| Number of products with errors: 15 | | |
|--|-----------------------------|--|
| Product | Test Failed | Description |
| CS_OFFL_SIR_FDM_220150101T010939_20150101T013209_B001 | Echo error | The Echo Rx1 Error flag is set, indicating a degraded raw echo |
| CS_OFFL_SIR_FDM_220150101T042825_20150101T042947_B001 | Echo error | The Echo Rx1 Error flag is set, indicating a degraded raw echo |
| CS_OFFL_SIR_FDM_220150101T121652_20150101T121706_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T121708_20150101T122234_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T135857_20150101T135955_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T153809_20150101T153914_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T153914_20150101T153929_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T154220_20150101T154459_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T154554_20150101T154559_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T155830_20150101T160748_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T161034_20150101T163206_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T163819_20150101T163942_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T163950_20150101T164358_B001 | Attitude correction missing | The attitude has not been corrected |
| CS_OFFL_SIR_FDM_220150101T164846_20150101T165906_B001 | Attitude correction missing | The attitude has not been corrected |
| CS OFFL SIR FDM 2 20150101T170054 20150101T171329 B001 | Attitude correction missing | The attitude has not been corrected |

6.6 L2 FDM Range Measurement Flags

Each product is checked to detect range measurements flagged by the processing chain as missing or containing errors.

1

15

Number of products with errors:

| Product | Test Failed | Description |
|---|---------------------------|--|
| CS_OFFL_SIR_FDM_220150101T172128_20150101T172152_B001 | OCOG Retracked Range Flag | The master fail flag is set by the OCOG call, for one or more records, indicating the values stored in fields #18, #19, #20 and #21 should be ignored for these records. |
| | | |

6.7 L2 FDM SWH and Backscatter Measurement Flags

Each product is checked to detect parameters related to SWH and sigma0 that are flagged by the processing chain as missing or containing errors.

 Number of products with errors:
 1

 Product
 Test Failed
 Description

 CS_OFFL_SIR_FDM_2_20150101T010939_20150101T013209_B001
 OCOG Backscatter Status Flag
 The master fail flag is set by the CFI call, for one or more records, indicating the values stored in fields #47, #48, #49 and #50 should be ignored for these records.

6.8 L2 FDM Geophysical Measurement Flags

Each product is checked to detect geophysical measurements flagged by the processing chain as missing or containing errors.

0

All

| Number of products with errors: 3 | | | | | |
|---|-------------------------------|---|--|--|--|
| Product | Test Failed | Description | | | |
| CS_OFFL_SIR_FDM_220150101T132903_20150101T135719_B001 | | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. | | | |
| CS_OFFL_SIR_FDM_220150101T151607_20150101T152333_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. | | | |
| CS_OFFL_SIR_FDM_220150101T172128_20150101T172152_B001 | Ocean Retracking Quality Flag | The Ocean Retracking Quality Flag is set indicating the CFI Ocean Retracker was not successfully executed for one or more records. | | | |

7. QCC Check

The QCC is a CryoSat facility that performs a primary survey of data products immediately after production by the PDS and LTA processing facilities. A list of the tests which raised errors or warnings is provided below.

| Product type | Nb. Products | Nb. QCC Reports | Nb. Valid | Nb. Warnings | Nb. Errors |
|--------------|--------------|-----------------|-----------|--------------|------------|
| SIR_FDM_1B | 170 | 0 | 0 | 0 | 0 |
| SIR_FDM_2 | 169 | 0 | 0 | 0 | 0 |

7.1 QCC Errors

Number of QCC reports with errors:

7.2 Missing QCC Reports

Number of products with missing QCC reports: