




1. Overview

Report Production Date:	22-Jan-2014	Check	Status	
	22-Jan-2014	Server check: science-pds.cryosat.esa.int	Nominal	
Data Used:	OFFLINE L1B and L2 Science	Server check: calval-pds.cryosat.esa.int	Nominal	
	Data	Product Software Check	Nominal	
	·	Product Format Check	Nominal	
		Product Header Analysis	Nominal	
		Auxiliary Data File Usage	See Section 5.3	
		Auxiliary Correction Check	See Section 4.4 and 5.4	
		Measurement Data Set Check	Nominal	

Miss	Mission / Instrument News			
22	2-Dec-2013	None		
23	B-Dec-2013	None		
24	-Dec-2013	Nothing planned		



The SIRAL instrument configuration for the day of acquisition is provided below.

SIRAL instrument(s) in use:	SIRAL - A
Star Tracker(s) in use:	Star Tracker 1 & 2

4.1 L1B Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a product file (.DBL).

Number of products with errors:

4.2 L1B Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the ground-segment processing chain.

Number of products with errors:

4.3 L1B Auxilary Data File Usage Check

Each product is checked for missing Data Set Descriptors wrt a pre-determined baseline and also to check the validity of Auxiliary Data Files is correct. Number of products with errors: 0

4.4 L1B Flagged Auxiliary Correction Error Check

Each product is checked to spot auxiliary corrections flagged by the ground-station processing chain as missing or containing errors

Number of products with errors:

Product	Test Failed
CS_OFFL_SIR_SAR_1B_20131223T115842_20131223T120029_B001	Dynamic atmosphere correction error
CS_OFFL_SIR_SAR_1B_20131223T175653_20131223T180222_B001	Dynamic atmosphere correction error
CS_OFFL_SIR_SIN_1B_20131223T000000_20131223T000353_B001	Dynamic atmosphere correction error
CS_OFFL_SIR_SIN_1B_20131223T055939_20131223T060102_B001	Dynamic atmosphere correction error

4.5 L1B Measurement Confidence Data Check

CryoSat L1B data includes a measurement confidence flag word (field 14) for each measurement record. The bit value of this flag indicates any problems when set.

Number of products with errors:

5. Level 2 Data Quality Check

5.1 L2 Product Format Check

Each product, retrieved and unpacked from the science server, is checked to ensure it consists of both an XML header file (.HDR) and a product file (.DBL). Number of products with errors:

5.2 L2 Product Header Analysis

For all products, a series of pre-defined checks are carried out on the MPH and SPH in order to identify any inconsistencies and/or errors raised by the ground-segment processing chain Number of products with errors: 0

5.3 L2 Auxiliary Data File Usage Check

Each product is checked for missing Data Set Descriptors wrt a pre-determined baseline and also to check the validity of Auxiliary Data Files is correct

Number of products with errors:

Product AUX File Comment CS_OFFL_SIR_GDR_2A_20131222T235214_20131223T013128_B001 CS_OPER_AUX_ORBDOR_20131221T215525_20131223 002325_0001 Coverage missing for intervals [2013-12-23T00:23:25, 2013-12-23T01:31:28]

5.4 L2 Flagged Auxiliary Correction Error Check

Each product is checked to spot auxiliary corrections flagged by the ground-station processing chain as missing or containing errors

4

1

Number of products with errors:

Product	Test Failed
CS_OFFL_SIR_SAR_2A_20131223T115842_20131223T120029_B001	Dynamic atmosphere correction error
CS_OFFL_SIR_SAR_2A_20131223T175653_20131223T180222_B001	Dynamic atmosphere correction error
CS_OFFL_SIR_SIN_220131223T000000_20131223T000353_B001	Dynamic atmosphere correction error
CS_OFFL_SIR_SIN_220131223T055939_20131223T060102_B001	Dynamic atmosphere correction error

5.5 L2 Measurement Quality Flag Check

CryoSat L2 data includes a quality flag word (field 43) for each 20-Hz measurement record. The bit value of this flag is an assessment of the measurement quality by the ground-segment processing chains

Presently, there are several common data Quality Flag errors raised by the Level 2 products which are either expected due to changes made to the IPF processor in Baseline B or else are due to known issues with the data processors. The investigation of the known issues are on-going and are due to be resolved with the next update of the Level 2 processors. All common known issues are summarised in the list below, followed by a table highlighting any additional issues which may arise from this test.

Freeboard Error: This Quality Flag is correctly set in all products as this parameter is currently not provided in the L2 products and the Freeboard value is presently set to the default value of -9999.

SARin x-track angle error: Currently there is an on-going investigation into the high number of errors from the 'SARIn x-track Error' Quality Flag over Antarctica.

Height error and Backscatter error: It has been noted that the number of errors arising from the 'Backscatter Error' and 'Height Error' Quality Flag is much higher than expected over land areas and this is currently part of an on-going investigation by expert teams.

6. QCC Check

The QCC is a CryoSat facility that performs a primary survey of data products immediately after production by the PDS and LTA processing facilities. A list of the tests which raised errors or warnings is provided below.

Nb. There is currently a discrepancy between the number of QCC reports and the number of products reported. This is a known issue and investigation is on-going.

0

Product type	Nb. Products	Nb. QCC Reports	Nb. Valid	Nb. Warnings	Nb. Errors
SIR_GDR_2A	15	0	0	0	0
SIR_LRM_1B	164	0	0	0	0
SIR_LRM_2	164	0	0	0	0
SIR_SAR_1B	121	0	0	0	0
SIR_SAR_2A	121	0	0	0	0
SIR_SIN_1B	113	0	0	0	0
SIR_SIN_2	113	0	0	0	0

6.1 QCC Errors

Number of products with QCC errors:

6.2 Missing QCC Reports

Number of products with missing QCC reports: All