
ENVISAT - AATSR

CYCLIC REPORT #111

	START	END
DATE	20TH JANUARY 2012	19TH FEBRUARY 2012
TIME	22:04:30	22:04:33
ORBIT #	51739	52170



Sea surface temperature variability off the tip of Oman on 16 February 2012. This false-colour AATSR image was taken during orbit 52116, using 3.7 micron band data with land and cloud masked in black.

prepared by/*préparé par* AATSR IDEAS and QWG team
reference/*réference*
issue/*édition* 1
revision/*révision* 0

date of issue/*date d'édition* 02 March 2012
status/*état*
Document type/*type de document* Technical Note
Distribution/*distribution*

A P P R O V A L

Title *titre*	AATSR Cyclic Report – Cycle 111	issue 1 *issue*	revision 0 *revision*
author *auteur*	Pauline Cocevar	date 02 March 2012 *date*	
approved by *approuvé par*		date *date*	

C H A N G E L O G

reason for change /*raison du changement*	issue/*issue*	revision/*revision*	date/*date*
		0	

C H A N G E R E C O R D

ISSUE: 1 REVISION: 0

reason for change/*raison du changement*	page(s)/*page(s)*	paragraph(s)/ *paragraph(s)*

TABLE OF CONTENTS

AATSR CYCLIC REPORT # 111 1

1 INTRODUCTION 1
1.1 Acronyms and Abbreviations 1

2 SUMMARY 2

3 SOFTWARE & AUX FILE VERSION CONFIGURATION 3
3.1 Software Version 3
3.2 Auxiliary Files 3
3.2.1 Status of Daily Visible Calibration Files 4
3.2.1.1 VC1 File Availability 4
3.2.2 Status of other Auxiliary Files 4

4 PDS STATUS 5
4.1 Instrument Unavailability 5
4.2 L0 Data Acquisition and L1B Processing Status 5
4.2.1 Orbits Affected by Poor Data Quality 6
4.3 L0 and L1B Backlog Processing Status 6

5 DATA QUALITY CONTROL 7
5.1 Monitoring of Instrument Parameters 7
5.1.1 Jitter 7
5.1.2 Sensor Temperature 8
5.1.3 Viscal 8
5.1.4 NEΔT 8
5.2 User Rejection 9
5.3 Software Problem Reporting 9
5.3.1 Existing SPRs that are still open 9
5.3.2 New SPRs since the last cyclic report 12
5.3.3 Closed SPRs 12
5.4 Monthly Level 3 Products 12

6 CALIBRATION/VALIDATION ACTIVITIES & RESULTS 16
6.1 Calibration 16
6.2 Validation 16

7 DISCLAIMERS 18

AATSR CYCLIC REPORT # 111

1 INTRODUCTION

The AATSR Cyclic Report is distributed by the AATSR IDEAS team to keep the AATSR community informed of any modification regarding instrument performances, the data production chain and the results of calibration and validation campaigns at the end of each Envisat 2010+ cycle, which consists of 431 complete orbits over the course of 30 days.

This document is available online at: http://earth.esa.int/pcs/envisat/aatsr/reports/cyclic/

1.1 Acronyms and Abbreviations

AATSR	Advanced Along Track Scanning Radiometer
APC	Antenna Pointing Controller
CR	Cyclic Report
DDS	Data Dissemination System
DMOP	Detailed Mission Operation Plan
DMS	Data Management System
EN-UNA-YYYY/#	Envisat Unavailability (plus year and number)
ESOC	European Space Operation Centre
GOSTA	Global Ocean Surface Temperature Atlas
HSM	High Speed Multiplexer
IDEAS	Instrument Data quality Evaluation and Analysis Service
IECF	Instrument Engineering and Calibration Facilities
IPF	Instrument Processing Facilities
LUT	Look Up Table
MPS	Mission Planning Schedule
NRT	Near Real Time
OCM	Orbit Control Manoeuvre
OBDH	On-board Data Handling
PDS	Payload Data Segment
PMC	Payload Management Computer
RAL	Rutherford Appleton Laboratory
SPR	Software Problem Reporting
SSR	Solid State Recorder
SW	Software
VISCAL	Visible Calibration

The AATSR list of acronyms and abbreviations is available at the following site:
http://envisat.esa.int/dataproducts/aatsr/CNTR5.htm#eph.aatsr.glossary

2 SUMMARY

Cyclic Report: 111

Cycle Start: 20th January 2012, 22:04:23 Orbit #: 51739

Cycle End: 19th February 2012, 22:04:30 Orbit #: 52170

The main activities during the cycle have been as follows:

- **ESRIN downtimes and delays**
  - 03 – 04 February 2012: Disruption to data acquisition and loss of data due to heavy snowfall and antenna problems (see section 4.2)
  - 12 – 14 February 2012: Problems connecting to the ESRIN internet and EO services
- **Kiruna downtimes and delays**
  - 13 February 2012: Planned maintenance causing some NRT delays
- **Unavailabilities – AATSR outgassing**

  Following an ENVISAT payload switch-off to correct a Service Module Memory anomaly, the opportunity was taken to conduct an AATSR outgassing. This took place over the following period:
  - 23 January 2012 07:28:00 to 26 January 2012 13:52:05

  AATSR was in STANDBY mode, so no channels were available for this time (orbits 51773 – 51820).

3 SOFTWARE & AUX FILE VERSION CONFIGURATION

3.1 Software Version

AATSR IPF for Level 1 and Level 2: Version 6.03

AATSR L2P Processor: Version 1.5.

3.2 Auxiliary Files

AATSR processing uses the following auxiliary files:

- Browse Product Lookup Data (ATS_BRW_AX)
- L1b Characterisation Data (ATS_CH1_AX)
- Cloud Lookup Table Data (ATS_CL1_AX)
- General Calibration Data (ATS_GC1_AX)
- AATSR Instrument Data (ATS_INS_AX)
- Visible Calibration Coefficients Data (ATS_VC1_AX)
- L1b Processing Configuration Data (ATS_PC1_AX)
- L2 Processing Configuration Data (ATS_PC2_AX)
- SST Retrieval Coefficients Data (ATS_SST_AX)
- LST Land Surface Temperature Coefficients Data (ATS_LST_AX)

Because the PC1 file contains the orbit period, two versions now need to be maintained after the mission extension orbit manoeuvres.

The latest filename for each auxiliary file in use in the PDS is as follows:

Product name
ATS_BRW_AXVIEC20020123_072338_20020101_000000_20200101_000000
ATS_CH1_AXVIEC20070720_093530_20020301_000000_20200101_000000
ATS_CL1_AXVIEC20101015_104659_20020301_000000_20200101_000000
ATS_GC1_AXVIEC20070720_093834_20020301_000000_20200101_000000
ATS_INS_AXVIEC20070720_094014_20020301_000000_20200101_000000
See below for VC1 files
ATS_LST_AXVIEC20101018_094830_20020301_000001_20200101_000000
ATS_PC1_AXVIEC20101015_101827_20020301_000000_20101021_235959
ATS_PC1_AXVIEC20101015_100604_20101022_000000_20200101_000000
ATS_PC2_AXVIEC20020123_074151_20020101_000000_20200101_000000
ATS_SST_AXVIEC20051205_102103_20020101_000000_20200101_000000

Table 3-1 Latest auxiliary files currently in use by the PDS

3.2.1 STATUS OF DAILY VISIBLE CALIBRATION FILES

3.2.1.1 VC1 File Availability

The following daily reflectance channel calibration files were not available during this cycle:

Date	Validity range		Comments
	From	To	
24/01/2012	22/01/2012	29/01/2012	No data available due to AATSR outgassing
25/01/2012	23/01/2012	30/01/2012	No data available due to AATSR outgassing
26/01/2012	24/01/2012	31/01/2012	No data available due to AATSR outgassing
28/01/2012	26/01/2012	01/02/2012	VC1 processing switched off
05/02/2012	03/02/2012	10/02/2012	No suitable files available to be processed
11/02/2012	09/02/2012	16/02/2012	IECF unavailable
12/02/2012	10/02/2012	17/02/2012	IECF unavailable
13/02/2012	11/02/2012	18/02/2012	IECF unavailable
18/02/2012	16/02/2012	23/02/2012	Not created due to planned power outage
19/02/2012	17/02/2012	24/02/2012	Not created due to planned power outage

Table 3-2 Unavailable VC1 files

This reporting period, there were multiple issues with the generation, delivery and dissemination of VC1 files, some planned and some unexpected.

One extended-range validity VC1 file was delivered to cope with expected outages:

Date	Validity range		Comments
	From	To	
25/01/2012	22/01/2012	06/02/2012	Extended-range validity file

Table 3-3 Extended-range VC1 file available

3.2.2 STATUS OF OTHER AUXILIARY FILES

No auxiliary files changed during this cycle.

4 PDS STATUS

4.1 Instrument Unavailability

AATSR data were unavailable due to instrument unavailability at the following times during the cycle:

UTC Start	UTC Stop	Reason	Reference	Planned
23/01/2012 07:28:00	26/01/2012 13:52:05	Envisat SM Memory Fault leading on to AATSR outgassing	EN-UNA-2012/0018	Yes

Table 4-1 Instrument unavailability during cycle 111

4.2 L0 Data Acquisition and L1B Processing Status

Week		Orbit		Availability (s)			Availability (%)		
#	Dates	Start	Stop	Inst Unav	L0 gaps	L1 gaps	Instrument	L0	L1
1	20 January 2012	51739	51825	282245	483	5574	45.55%	45.46%	44.39%
2	26 January 2012	51825	51911	0	0	0	100.00%	100.00%	100.00%
3	01 February 2012	51911	51998	0	25934	0	100.00%	95.00%	95.00%
4	07 February 2012	51998	52084	0	0	0	100.00%	100.00%	100.00%
5	13 February 2012	52084	52170	0	0	0	100.00%	100.00%	100.00%

Table 4-2 Instrument and data unavailability weekly summary for Cycle 111

The instrument was available for 89.11% of the time during the cycle.
The L0 data were available for 88.09% of the time during the cycle.
The L1b data were available for 87.88% of the time during the cycle.

The following L0 data were missing from this cycle:

UTC Start	UTC Stop	Duration (s)	Orbit Start	Orbit End
23/01/2012 07:19:57	23/01/2012 07:28:00	483	51773	51773
03/02/2012 01:36:02	03/02/2012 04:29:45	10423	51927	51927
03/02/2012 04:53:40	03/02/2012 04:58:36	296	51929	51929
03/02/2012 05:47:57	03/02/2012 06:09:40	1303	51930	51930
03/02/2012 22:49:55	03/02/2012 23:19:12	1757	51940	51940
04/02/2012 03:49:50	04/02/2012 07:12:25	12155	51943	51943

Table 4-3 ATS_NL__0P missing data during Cycle 111

Data missing at L0 are also missing at L1B. The following L1B data were additionally missing from this cycle:

UTC Start	UTC Stop	Duration (s)	Orbit Start	Orbit End
26/01/2012 13:52:05	26/01/2012 15:24:59	5574	51820	51821

Table 4-4 ATS_TOA_1P missing data during Cycle 111

4.2.1 ORBITS AFFECTED BY POOR DATA QUALITY

The information reported in Section 4.2 does not consider the quality of the data, only whether or not it is available.

During this cycle, the following orbits contained frames suffering from bad/missing telemetry:

- 51929-30, 39-40 (03 Feb 2012)
- 52040 (10 Feb 2012)
- 52168 (19 Feb 2012)

The cloud-clearing algorithm failed on the following orbits during this cycle:

- 51921 (02 Feb 2012), southern Indian ocean
- 51933 (03 Feb 2012), Tasman Sea
- 52002 (08 Feb 2012), south Pacific
- 52028, 30 (10 Feb 2012), off the coast of Vietnam, and south-east Pacific
- 52042 (11 Feb 2012), between China and Taiwan
- 52097 (14 Feb 2012), north-east Atlantic
- 52111 (15 Feb 2012), central-north Pacific
- 52123 (16 Feb 2012), southern Indian ocean

4.3 L0 and L1B Backlog Processing Status

There is no update available on the status of backlog processing.

5 DATA QUALITY CONTROL

5.1 Monitoring of Instrument Parameters

5.1.1 JITTER




Figure 5-1 Jitter trend from mission start




Figure 5-2 Jitter trend since the mission extension

The plots show the jitter-trend since the start of the mission and since the recent mission extension, against both orbit-number and cycle-number. The mean jitter-rate (per-orbit) is shown in blue and the maximum rate per orbit in red. The green horizontal line shows the nominal mean jitter-level achieved for much of the mission.

The jitter plot for the extended mission shows no significant sustained change in the mean jitter-rate variation over this cycle compared to that in recent cycles.

5.1.2 SENSOR TEMPERATURE

The detector temperature plots for Cycle 111 can be found at:
http://www.aatsrops.rl.ac.uk/EDSX/CyclePlots/DetTemps111.pdf

Detector temperatures have been nominal throughout this cycle, given the outgassing of 23-26 January 2012.

5.1.3 VISCAL

NRT calibration quality for the AATSR reflectance channels has been maintained throughout the cycle. As usual, no reflectance channel calibration is available during an outgassing. The list of "orbital" VC1 files delivered for this cycle can be found at: http://www.aatsrops.rl.ac.uk/EDSX/CyclePlots/VC-111.txt

5.1.4 NE∆T

Information on the NE∆T for Cycle 111 is shown in Table 5-1. Figure 5-3 shows the trend since launch.

	Hot BB		**Cold BB**	
	T = 300.85 K		T = 261.82 K	
	Count	**NE∆T (mK)**	**Count**	**NE∆T (mK)**
12 µm	1.54	32.4	1.16	34.0
11 µm	1.48	30.4	1.09	33.2
3.7 µm	2.47	31.5	1.18	76.0

Table 5-1 NE∆T information for 10 February 2012 (Cycle 111)




Figure 5-3 Time series of NE∆T since launch

5.2 User Rejection

There were no user rejections during this cycle.

5.3 Software Problem Reporting

This section describes the new and open SPRs, their potential impact on the data quality, and any SPRs that have been closed.

5.3.1 EXISTING SPRS THAT ARE STILL OPEN

The following SPRs are still open:

Wrong REF_DOC in MPH of AATSR products
NA-PR-10-05334
As a result of the AMALFI-2 pilot project, it has been discovered that the REF_DOC field in the MPH of AATSR products is different from the product specification name.
1) The REF_DOC should follow “AA-BB-CCC-DD-EEEE_V/I”, 23 characters where AA-BB-CCC-DD-EEEE is the ESA standard document number and V/I is the

volume/issue.
2) The referenced product spec is still 3/K. whilst the one applicable, and also referenced in the SRN of 6.03 is 4/A.

AATSR Child Products contain insufficient number of ADS records
NA-PR-08-03912
The number of ADS records present in AATSR child products is insufficient for processing of the entire product. Users are currently advised to order products of at least 1 granule longer to obtain all required ADS records. Excluding the SQADS and the scan pixel x and y ADS, the DPM requires that for AATSR full resolution products, the number of records in the ADS shall be one greater than the number of MDS granules in the product. Child products are currently produced with a number of ADS records equal to the number of MDS granules in the product. In the case of the SQADS, this is sampled only every 512 rows, rather then every 32, so in order to provide coverage for every granule in a child product, the number of SQADS records strictly required depends on the length of the child product and where the child product starts in relation to the 512 record boundaries. Parent products by definition start on a 512 record boundary, but child products need not. If we define a product segment of 512 consecutive rows (=16 granules) as a frame, then the number of SQADS records required in the child product is equal to the number of frames overlapped by the child product. For the case of the Scan Pixel x and y ADS, the records represent instrument scans, not image rows. There is no simple algorithm to define the number of records from the parent product that should be included in the child product.

Update to AATSR Child product generation requirements
NA-PR-08-04015
The 'Child Product Generation Requirements' on pages 520-521 of the document 'PDS Technical Specification for Maintenance and Evolution' (PO-RF-CSF-GS-20437) currently reads:
"For time extraction, for each data set in the parent product, the time stamp of the DSRs shall be compared to that of the requested start time (t0) segment. The first DSR extracted from each data set to form the new child data set is the one with a time stamp immediately preceding or equal to t0. The last DSR extracted from each DS is the one immediately preceding t1."
To ensure that a sufficient number of Auxiliary Data Set Records are present in AATSR child products, the requirement should be changed to read as follows:
"For time extraction, for each data set in the parent product, the time stamp of the DSRs shall be compared to that of the requested start time (t0) segment. The first DSR extracted from each data set to form the new child data set is the one with a time stamp immediately preceding or equal to t0. The last DSR extracted from each DS is the one immediately preceding t1.
For AATSR data, the last ADS DSR extracted from each DS is the one whose time label is equal to or greater than t1 provided such a DSR exists, otherwise the last ADS DSR in the product."

Processing of L1/L2 fails with product ATS_NL__0PNPDE20100515_214836_000061722089_00272_42911_1524.N1
IDEAS-PR-10-05411
The problem does not occur in prototype, but in PDGS operational chain and in Gamme validation platform. Processing the following L0 product to L1 and L2 fails ATS_NL__0PNPDE20100515_214836_000061722089_00272_42911_1524.N1.
Please consider that same error occurs also IN GAMME test environment.
19.08.2010 -Feedback from ELCA:"There is just a debug option that has to be removed from the optimization options while building AATSR IPF. When building the IPF with the correct options this error does not occur and the processing completes and generates L1/L2 products."

AATSR MPH OSV field does not agree with SPH auxiliary filename
IDEAS-PR-11-05568
We are noticing that, on occasion, the OSV source field in the MPH does not agree with the auxiliary data file name given in the SPH. For example: (1) in product ATS_TOA_1PRUPA20110527_222624_000065273103_00029_48319_8139.N1, the MPH gives the OSV source as "FR", while the SPH reports that the file used was actually an FPO file (AUX_FPO_AXVPDS20110528_102115_20110527_190825_20110606_212212); (2) in product ATS_TOA_1PNPDE20110526_021402_000066813103_00003_48293_4416.N1, the MPH gives the OSV source as "FP", while the SPH reports that the file used was actually an FRO file (AUX_FRO_AXVPDS20110528_102115_20110524_221000_20110527_005000). Note that this does not always happen, but seems to be related to when files are processed using a non-anticipated file type, but not in every instance. ELCA's analysis: "The solution is to compute in output product's MPH the OSV value based on the orbit file passed in the job order instead of using the L0 MPH's value."

AATSR: Reduce the logging noise by removing the warning on jitter
IDEAS-PR-11-05587
The requirement is that the scan jitter warnings are disabled (this information is present in the products themselves, and we are aware and monitoring jitter levels from the operational data anyway). There are numerous warnings of this type, even in the logs from a successful processing run, so they prevent the log from being easily read to diagnose any problems.
We see this also useful for PDGS, since the logging size will reduce.
It is agreed that this change shall be included in the IPF version for the reprocessing.

AATSR: AATSR products non conformance to FODP
IDEAS-PR-11-05594
From O&M: PBI000000004179: The AATSR Flight Operations and Data Plan (FODP), PO-PL-ESA-AT-0152, Issue 2 Revision 5 dated 22 November 2001 defines the meaning of "consolidated" in Appendix B.1 as follows: "… time-ordered, no overlap nor data gap except when the instrument is not operated …", and for

Level 0 there should be sufficient overlap only so that the higher level products can be chopped "… ANX to ANX …". The FODP is part of the high level agreement between ESA and Defra and so can be taken as the definitive requirement for AATSR products. We would like to enquire as to the current definition applied to consolidated products and ask that a change be proposed and the impact of such a change evaluated.
This PBI is a copy of the PBI1161. The PBI1161 was corrected via a CRQ but the delivery introduced other problem so the CRQ was discarded. Consequently, the problem described by PBI1161 is still present.

5.3.2 NEW SPRS SINCE THE LAST CYCLIC REPORT

There were no new SPRs opened since the last Cyclic Report.

5.3.3 CLOSED SPRS

There were no SPRs closed since the last Cyclic Report.

5.4 Monthly Level 3 Products

The following plots have been generated from the available Meteo products acquired for January 2012. These consist of 397 products from orbits 51452 to 51897. Figure 5-5, Figure 5-6, Figure 5-7 and Figure 5-8 show the SST average in dual and nadir views, the standard deviation and the number of contributory orbits for January 2012. Figure 5-9 and Figure 5-10 show anomalies of the monthly averages from an SST climatology. Please note that individual colour scales for each plot are not available, however the scheme used is given in Figure 5-4, and the data ranges of each plot are specified in the accompanying caption.



Figure 5-4 This is the colour scheme used for the following plots, running linearly from left to right with increasing magnitude




Figure 5-5 Monthly average Dual View SST, with a data range of 270 - 305 Kelvin for January 2012




Figure 5-6 Monthly average Nadir View SST, with a data range of 270 – 305 Kelvin for January 2012




Figure 5-7 Standard deviation of the monthly average SST with a colour key range of 0 to 5 K, and a maximum value of 9 K for January 2012




Figure 5-8 Number of contributory orbits to the calculation of the SST, with a colour key range of 0 to 17 (maximum value), for January 2012

Monthly SST anomaly maps, referenced to the GOSTA climatology dataset, are now being produced (beginning at Cyclic Report #106). Figure 5-9 and Figure 5-10 display the SST anomalies for dual- and nadir-view SSTs for January 2012, respectively. The anomaly scale runs from -10 K (blue) to +10 K (red). Orbits affected by cloud-clearing failures, which would show up as strong blue in the anomaly maps, are listed in Section 4.2.1. Any orbit which is found to have exhibited a cloud-clearing failure is also mentioned in the AATSR Daily Report at: http://earth.eo.esa.int/pcs/envisat/aatsr/reports/daily/




Figure 5-9 Anomaly map of Dual View SST for January 2012




Figure 5-10 Anomaly map of Nadir View SST for January 2012

6 CALIBRATION/VALIDATION ACTIVITIES & RESULTS

6.1 Calibration

No calibration results were reported during this cycle.

6.2 Validation

The Met Office has validated the AATSR dual-view SST data using the global network of *in situ* drifting buoy SST data; the results for Cycle 111 being shown in Figure 6-1. The updated SST coefficients released in December 2005 were used in the AATSR SST retrievals.




Figure 6-1 Comparison of daily mean difference between 10´ AATSR SST values and *in situ* drifting buoy SST for Cycle 111. Data provided by the Met Office

During cycle 111, there were 692 night time match-ups, with a mean (UL derived dual-view skin SST minus buoy SST) of -0.03 K, standard deviation 0.26 K, and a mean (dual-view depth SST minus buoy SST) of +0.10 K, standard deviation 0.25 K. A total of 585 daytime match-ups were found, with a mean (UL derived dual-view skin SST minus buoy SST) of +0.05 K, standard deviation 0.31 K, and a mean (dual-view depth SST minus buoy SST) of +0.20 K, standard deviation 0.32 K. As these data are comparisons of a single point buoy measurement against a much larger spatially averaged value they are not a true indicator of AATSR's accuracy and are used to show consistency of data quality between cycles.




Figure 6-2 Plot of daily number of match-ups between 10´ AATSR SST values and *in situ* buoy SST for Cycle 111. Data provided by the Met Office




Figure 6-3 Map showing global distribution of match-ups between 10´ AATSR SST values and *in situ* buoy SST for Cycle 111. The cyan dots indicate a match-up to a drifting buoy. Data provided by the Met Office

7 DISCLAIMERS

No new disclaimers have been issued during this cycle.