

PRELIMINARY REPORT OF 040321

ATTENTION: This report is automatically generated no comments are provided on data analysis

last update on Sun Mar 21 12:40:01 GMT 2004

1. [Introduction](#)
2. [Summary](#)
 - [Instrument Unavailability](#)
 - [Browse Visual Inspection](#)
 - [Module Stepping Results](#)
 - [Data Analysis](#)
3. [Module Stepping](#)
4. [Internal Calibration pulses](#)
 - [Daily statistics \(row 3 and 24\)](#)
 - [Cyclic statistics \(row 3 and 24\)](#)
 - [cal pulses monitoring \(all rows\)](#)
5. [Raw Data Statistics](#)
 - [raw data mean I and Q](#)
 - [raw data stdev I and Q](#)
 - [raw gain imbalance](#)
6. [Wave Doppler analysis](#)
 - [Doppler evolution versus ANX](#)

1 - Introduction

This report is based on the analysis of wave mode level-1 cross spectra (ASA_WVS_1P) products, which are the available few hours after the acquisition, on the high rate browse (BP) products and on the Module Stepping (MS) product.

2 - Summary

2.1 - Instrument Unavailability

No unavailabilities during the reported period.

2.2 - Browse Visual Inspection

2.3 - Data Analysis

-Stable wave internal calibration pulses gain and phase.

-Stable raw data statistics.

-Nominal Doppler behavior.

3 - Module Stepping Mode

The MS mode provides an internal health check on an individual module basis.

The purpose of this mode is to identify to identify any malfunctionning modules and to identify modules for which calibration offsets are to be applied.

No anomalies observed on available MS products:

Polarisation	Start Time
V	20040320 202249
H	20040320 202129

MSM in V/V polarisation

Pre-launch Reference	DDS-B (2003-06-12) reference
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

MSM in H/H polarisation

Pre-launch Reference	DDS-B (2003-06-12) reference
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

4 - Internal calibration Results

No anomalies observed.

4.1 - Daily statistics



4.2 - Cyclic statistics



4.3 - cal pulses monitoring (all rows)



5 - RAW data statistics

No anomalies observed.

5.1 - Input mean I/Q

channel	stat	DSS-B
MEAN I	mean	0.000472174
	stdev	2.34875e-07
MEAN Q	mean	0.000493370
	stdev	2.60280e-07



5.2 - Input stdev I/Q

channel	stat	DSS-B
STDEV I	mean	0.127546
	stdev	0.00112553
STDEV Q	mean	0.127780
	stdev	0.00113845



5.3 - Gain imbalance I/Q

6 - Doppler Analysis

Preliminary report. The data is not yet controlled

6.1 - Unbiased Doppler Error


Evolution of unbiased Doppler error (Real - Expected)
Ascending
Descending

6.2 - Absolute Doppler


Evolution of Absolute Doppler
Ascending
Descending

6.3 - Doppler evolution versus ANX


Average P1



Average p2




Average p3




rows: **_ 3 _ 7 _ 11 _ 15 _ 19 _ 22 _ 24 _ 28**

Average P1




21-Mar

Average p2



21-Mar

Average p3




21-Mar

rows: — 3 — 7 — 11 — 15 — 19 — 22 — 24 — 28


No anomalies observed.








- Stable wave internal calibration pulses gain and phase.
- Stable raw data statistics.
- Nominal Doppler behavior.











The MS mode provides an internal health check on an individual module basis.
The purpose of this mode is to identify any malfunctionning modules and
to identify modules for which calibration offsets are to be applied.
No anomalies observed on available MS products:

No anomalies observed.



Reference:	2003-06-12 14:08:52 H	RxGain
Test	: 2004-03-20 20:21:29 H	
		1
		2
		3
		4
		5
		6
		7
A1	A3	B1
B3	C1	C3
D1	D3	E1
		E3
		8
		9
		10
		11
		12
		13
		14
		15
		16
		17
		18
		19
		20
		21
		22
		23
A2	A4	B2
B4	C2	C4
D2	D4	E2
		E4
		24
		25
		26
		27
		28
		29
		30
		31
		32

Reference: 2001-02-09 14:08:23 V RxGain

Test : 2004-03-20 20:22:49 V

A 3D surface plot showing RxGain across a grid of 16 points (A1-E4). The vertical axis represents RxGain from 1 to 32. The horizontal axes are labeled A1 through E4. The plot shows varying levels of signal strength across the grid, with higher values generally appearing in the lower-left and middle sections.

Reference:	2001-02-09 13:50:42 H	RxPhase							
Test	: 2004-03-20 20:21:29 H								
A1	A3	B1	B3	C1	C3	D1	D3	E1	E3
A2	A4	B2	B4	C2	C4	D2	D4	E2	E4


Reference:	2003-06-12 14:08:52 H	RxPhase							
Test	: 2004-03-20 20:21:29 H								
A1	A3	B1	B3	C1	C3	D1	D3	E1	E3
1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32								
A2	A4	B2	B4	C2	C4	D2	D4	E2	E4




Reference: 2001-02-09 14:08:23 V RxPhase




Test : 2004-03-20 20:22:49 V

Reference: 2003-06-12 14:10:32 V RxPhase

Test : 2004-03-20 20:22:49 V







Reference: 2003-06-12 14:08:52 H

Test : 2004-03-20 20:21:29 H

Reference: 2003-06-12 14:10:32 V


Test : 2004-03-20 20:22:49 V


Reference: 2003-06-12 14:08:52 H TxPhase
Test : 2004-03-20 20:21:29 H

A1 A3 B1 B3 C1 C3 D1 D3 E1 E3

A2 A4 B2 B4 C2 C4 D2 D4 E2 E4

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32





No unavailabilities during the reported period.

