

Customer : ESRIN Document Ref : IDEAS+-VEG-OQC-REP-2497

Contract No : 21525/08/I-OL Issue Date : 15 January 2016

WP No : 14500 Issue : 1.0

Title : IDEAS+ - SMOS Public Monthly Report - January 2016

Abstract : This document provides a summary of the status and performance of SMOS over the

course of the reporting month.

Author : Accepted :

IDEAS SMOS QC Team R. Crapolicchio on behalf of

ESA EOP-GMQ

Distribution :

Hard Copy File:

Filename: IDEAS+-VEG-OQC-REP-2497_v1.0.doc

Copyright © 2015 Telespazio Vega UK Ltd.

All rights reserved.

No part of this work may be disclosed to any third party translated reproduced copied or disseminated in any form or by any means except as defined in the contract or with the written permission of Telespazio Vega UK Ltd..

Telespazio Vega UK Ltd.
350 Capability Green, Luton, Bedfordshire, LU1 3LU, United Kingdom
Tel: +44 (0)1582 399 000 Fax: +44 (0)1582 728 686
www.vegaspace.com



TABLE OF CONTENTS

1.	EXECUTIVE SUMMARY	5
_		
2.		
2.1	Structure of the Document	
2.2	Definitions of Terms	6
3.	INSTRUMENT STATUS	9
3.1	Instrument health	
3.2	Instrument unavailabilities and anomalies	9
4.	DATA SUMMARY	11
4.1		
4.2		
	4.2.1 Processor updates	
	4.2.2 Processor Status	
	4.2.3 Schema updates	
	4.2.4 Schema status	
	4.2.5 Aux file updates	
4.3		
4.4		
4.5		
4.6	Product Quality Disclaimers	15
5.	LONG-TERM ANALYSIS	17
5.1		
5.2	·	
6.	PRODUCT QUALITY ANALYSIS	34
7.	ADF CONFIGURATION AT THE END OF THE REPORTING PERIOD	35
ΔΡ	PENDIX A CONFIGURATION DOCUMENT LIST	37

AMENDMENT POLICY

This document shall be amended by releasing a new edition of the document in its entirety. The Amendment Record Sheet below records the history and issue status of this document.

AMENDMENT RECORD SHEET

ISSUE	DATE	DCI No	REASON
1	15 February 2016	N/A	First release



This Page is Intentionally Blank

1. EXECUTIVE SUMMARY

This is the routine Soil Moisture and Ocean Salinity (**SMOS**) Monthly Public Report containing a summary of the instrument health, product quality status and updates to SMOS processing and AUX files during January 2016.

The instrument health during January was found to be nominal although the LICEF A10 shows and increase of temperature from the 10th of January 2016. Regarding this, the quality of the data is being closely monitored, and for the moment, no degradation is apparent. There were four unavailabilities reported during the reporting period that translate into time intervals with data loss. The list of unavailabilities is included in the section 3.2.

The data quality during January was found to be nominal, with the exceptions listed in section 4.5. These degraded periods have been induced either by instrument anomalies or unavailability of dynamic auxiliary files.



2. INTRODUCTION

2.1 Structure of the Document

After this introduction, the document is divided into a number of major sections that are briefly described below:

1 Executive summary

The executive summary covers the main findings from the report.

2 Introduction

A list of referenced documents and definitions of terms are available.

3 Instrument status

This section covers the instrument health and unavailabilities from this reporting period.

4 Data Summary

This section covers reprocessing, updates to processors and aux files as well as a data coverage summary.

5 Long Term Analysis

Long-term analysis of the instrument calibration and data quality are provided in this section.

2.2 Definitions of Terms

The following terms have been used in this report with the meanings shown.

Term	Definition		
CMN	Control and Monitoring Node, responsible for commanding the receivers, reading their physical temperatures and telemetry and the generation of the synchronization signal (local oscillator tone) among receivers.		
CCU	Correlator and Control unit, instrument computer on- board		
DPGS	Data Processing Ground Segment		
ESL	Expert Science Laboratory		
IC4EC	Internal Calibration for External calibration. Calibration sequences for the instrument monitoring and calibration of science data acquired in external target pointing.		
IDEAS+	Instrument Data quality Evaluation and Analysis Service, reporting to the ESA Data Quality and Algorithms		



IDEAS+-VEG-OQC-REP-2497 Issue 1.0

Management Office (EOP-GQ), responsible for quality of data provided to users including the data calibration and validation, the data processing algorithms, and the routine instrument and processing chain performances.

IPF Instrument Processor Facility

L2SM Level 2 Soil Moisture

MM Mass Memory

OCM Orbit Correction Manoeuvre

PMS Power Measurement System

RFI Radio Frequency Interference

N/A Not applicable



This Page is Intentionally Blank

3. INSTRUMENT STATUS

3.1 Instrument health

The current instrument status is that all the **instrument** subsystems are working correctly. The current configuration of the instrument is that the arm A and the arm B are working in nominal side and arm C is in the redundant side.

Table 3-1 History of instrument problems and mode changes

Start	Stop	Description
11 January 2010 12:07z Orbit 1013	N/A	Arm A changes from redundant to nominal side. That operation is to avoid the malfunction of one of the redundant CMNs of the arm.
12 January 2011 09:15z Orbit 6278	N/A	Arm B changes from redundant to nominal side. That operation is to avoid the malfunction of one of the redundant CMNs of the arm.

3.2 Instrument unavailabilities and anomalies

The unavailabilities and anomalies listed in Table 3-2 occurred during the reporting period. A full list of unavailabilities can be found in the Mission Status section on the SMOS Earthnet website (https://earth.esa.int/web/guest/missions/esa-operational-eomissions/smos/content/-/asset publisher/t5Py/content/mission-status-7060)

During these unavailabilities and anomalies the instrument may have either not collected data or may have collected corrupt data which may not have been processed to higher levels. Table 4-5, Table 4-6 and Table 4-7 provide details of the data which has been affected by gaps and quality degradation respectively.

Table 3-2 SMOS unavailability list

Start Time	Stop Time	Unavailability Report Reference	Planned	Description
02/01/2016 02:29	02/01/2016 03:38	FOS-1190	No	MM Latch-up

IDEAS+-VEG-OQC-REP-2497 Issue 1.0



IDEAS+ SMOS Public Monthly Report - January 2016

03/01/2016 03:30	03/01/2016 03:34	FOS-1204	No	CCU Reset
05/01/2016 20:38	05/01/2016 20:41	FOS-1200	No	CCU Reset
06/01/2016 08:02	06/01/2016 08:25	FOS-1202	Yes	CCU Recovery

4. DATA SUMMARY

4.1 Reprocessing activities

The information regarding to data reprocessing activities (REPR data type) during the reporting period are:

1) None

The information regarding to the data regeneration activities (OPER data type) during the reporting period are:

1) On 6th of January 2016 there was a gap between 06:24:00z and 11:54:00z due to a hardware anomaly in L0 processing facilities. Afterwards, the L0 products were recovered and the affected data were reprocessed. This reprocessing involves the reprocessing of the CORD0 data from 20160106T000601 to 20160107T100846, and the reprocessing of the science data (from L0 and up to L2) with sensing times between 20160106T022828 and 20160107T065301.

The information regarding to past version 62x data reprocessing activities (REPR data type) are:

- 1) The second SMOS mission reprocessing for L2 v62x finished the 31st December. Sensing time of the reprocessed data goes from 12th January 2010 to 14th July 2015.
- 2) The second SMOS mission reprocessing for L1 v62x finished the 25th June 2015. Sensing time of the reprocessed data goes from 12th January 2010 to 05th May 2015. Data set is available for the SMOS user community since 25th June 2015 (see the SMOS news: https://earth.esa.int/web/guest/missions/esa-operational-eo-missions/smos/news/-/article/smos-level-1-algorithm-baseline-v620-reprocessed-dataset-now-available).

The SMOS data users are strongly encouraged to consult the level 1 read-me-first note before using the SMOS data. The level 1 read-me-first note is available here: https://earth.esa.int/documents/10174/1854503/SMOS L1OPv620 release note

The information regarding to the past version V62x data regeneration activities (OPER data type) are:

- On December 2015, the next periods were regenerated from L1C to L2 due to VTEC_P delay: the period from 20151206T005504 to 20151206T041830 and the period from 20150719T005448 to 20150720T024908.
- 2) On 15th of August 2015 a hardware anomaly caused a TLM_MIRA1A order to fail due to timeout. Therefore, a gap in science and in calibration (CSTD1A) was introduced. The next data types and periods has been regenerated: TLM_MIRA1A at 20150815T031323, CSTD1A files with times between 20150815T003625 and 20150815T214626, affected science (MIR_SC_F1A, MIR_SC_F1B, MIR_SCLF1C, MIR_SCSF1C, MIR_BWLF1C and MIR_BWSF1C) between 20150815T023400 and 20150815T050753.
- 3) Due to an anomaly in the NIR calibration on the 3rd of June 2015, the next data types has been regenerated from 2015-06-03 06:43z to 2015-06-12 08:14z: MIR_SC_F1A, MIR_SC_F1B, MIR_SCLF1C, MIR_SCSF1C, MIR_BWLF1C and MIR_BWSF1C.



- 4) A hardware anomaly in DPGS systems introduced a large delay in the production. As a consequence some CSTD1A orders were dropped due time-out. This introduced bad-consolidated calibration in the system, with some LO gaps, which has impacted the quality of the data severely (no local oscillator calibration). Data from 20150713T194909z until 20150714T032238z is affected. All data was regenerated successfully from L0 up to L1C; L2 is still affected by this anomaly (see section 4.6).
- 5) Period from 29 May 2015 to 31 May 2015 have been regenerated up to L2 since one of the DPGS processing nodes (PWF-5) induced several science and calibration gaps for the reported period.

The information regarding the past version V5xx data regeneration and reprocessing activities (OPER and REPR data type) are available in the monthly report of April 2015.

4.2 Processing changes

4.2.1 Processor updates

No processor updates have been conducted during the reporting period.

4.2.2 Processor Status

At the end of the reporting period, the Processing Facility is using the following processors:

Table 4-1 Instrument Processors status

Processor	Version
L1OP	620 (L1a/L1c/NIRCAL)
	621 (L1b/CAL_1A)
L2OS	622
L2SM	620

Table 4-2 Pre- and Post-processors status

Processor	Version
ECMWFP	318
VTECGN	311
LAI pre-processor	307
OSCOTT	624

L2 Post-processors	510

4.2.3 Schema updates

No schema changes have been conducted during the reporting period.

4.2.4 Schema status

At the end of the reporting period, the schema version of the datablock of the products generated and distributed through SMOS dissemination service is:

Table 4-3 Schema version status

Product type	Version
MIR_SC_F1B	400
MIR_SCSF1C	400
MIR_SCLF1C	400
MIR_BWSF1C	400
MIR_BWLF1C	400
MIR_SMUDP2	400
MIR_OSUDP2	400
AUX_ECMWF_	300

The schema packages are available from the SMOS Global Mapping Tool (GMT) webpage:

https://earth.esa.int/web/guest/software-tools/-/asset_publisher/P2xs/content/gmt-smos-global-mapping-tool

Further information about the product format is available in the level 1 and level 2 Product specification documents available here: https://earth.esa.int/web/guest/missions/esa-operational-eo-missions/smos/content/-/asset_publisher/t5Py/content/data-types-levels-formats-7631

4.2.5 Aux file updates

The following quasi-static AUX files were disseminated to the processing stations this reporting period. The status of the quasi-static AUX files at the end of the reporting period is in the section 7.

SM_OPER_AUX_BULL_B_20151102T000000_20151202T235959_120_001_3

Start sensing time at L1 processor: N/A



Justification: Bulletin Update including values from November 2015 and the prediction for December 2015. Its usage is intended for reprocessing.

SM_OPER_AUX_BULL_B_20151102T000000_20500101T000000_120_001_3

Start sensing time at L1 processor: 2016-01-05 03:57:30z

Justification: Bulletin Update including values from November 2015 and the prediction for December 2015. Its usage is intended for the nominal production.

4.3 Calibration Events Summary

The following table summarizes the major calibration activities conducted during the reporting period. The Local Oscillator calibration is not included in the table since occurs periodically every 10 minutes. The short calibrations are acquired weekly since 2011-03-24 and they are currently used in the nominal processing chain.

Table 4-4 Calibration summary

Date	Start Time	Stop Time	Calibration	Comments
06/01/2016	03:09:31z	04:31:44z	NIR-Warm	Nominal Brightness temperature: 3.6467 K RMS: 0.059 K Moon Elevation: -36.2037 Sun Elevation: 9.961987 Right Ascension:12.3656 Declination:-16.9811
07/01/2016	13:31:00z	13:32:44z	Short	Nominal
14/01/2016	12:18:00z	12:19:44z	Short	Nominal
20/01/2016	00:44:04z	02:06:17z	NIR-Warm	Nominal Brightness temperature: 3.6523 K RMS: 0.0711 K Moon Elevation: 36.4201 Sun Elevation: 9.98125 Right Ascension: 26.2852 Declination: -15.6368
21/01/2016	09:25:00z	09:26:44z	Short	Nominal
28/01/2016	08:12:00z	08:13:44z	Short	Nominal

4.4 Data Coverage Summary

Where instrument unavailabilities or anomalies have occurred during this reporting period, gaps in data coverage may have occurred. A list of the gaps due to a permanent data loss is given in Table 4-5 by product level. On the other hand, a list of gaps due to operational problems is given in Table 4-6. The latter gaps may be recovered when the problem is fixed.

The science data gaps due to the execution of calibration activities are not listed in this section.

Table 4-5 Data loss summary

Start	Finish	Data Level	Comments
02/01/2016 02:29z	02/01/2016 03:38z	All Products	MM Latch-up (FOS-1190)
03/01/2016 03:30z	03/01/2016 03:34z	All Products	CCU Reset (FOS-1204)
05/01/2016 20:38z	05/01/2016 20:41z	All Products	CCU Reset (FOS-1200)
06/01/2016 08:02z	06/01/2016 08:25z	All Products	CCU Recovery (FOS-1202)

Table 4-6 Operational gaps summary

Start	Finish	Data Level	Comments
22/01/2016 20:29z	22/01/2016 21:16z	L1C and above	Failed product with wrong ASC/DES flag.

4.5 Summary of degraded data

In January 2016, SMOS data was affected by the following instrument and processing anomalies which have had a detrimental effect on the data quality.

Table 4-7 Summary of degraded data

Start	Finish	Affected products	Problem Description
N/A	N/A	N/A	N/A

4.6 Product Quality Disclaimers

The following product disclaimers affects the data generated in the reporting period:



Table 4-8 Summary of product quality disclaimers

Date	Product level	
N/A	L1 L2	Due to a software anomaly in the Level 0 processor, the <i>Cycle, orbit relative and orbit absolute</i> fields in all the product headers are incorrectly set. Those values are annotated in the headers of all the higher level products.
3 June 2015 until 12 June 2015	L2	Due to an anomaly in the NIR calibration occurred on 3 June SMOS data from sensing time 2015-06-03 06:43 UTC to sensing time 2015-06-12 08:14 UTC are degraded. The L1C data has been regenerated and disseminated to the users by the nominal SMOS data dissemination service. The L2 degraded data set will be corrected in the next level 2 reprocessing campaign. For more information see the SMOS news here.
20150713T1 70803z until 20150714T0 32238z	L2	A hardware anomaly in DPGS systems introduced a large delay in the production. As a consequence some CSTD1A orders were dropped due time-out. This introduced bad-consolidated calibration in the system, with some Local Oscilator gaps, which has impacted the quality of the data severely (no local oscillator calibration). Even though L1 has been reprocessed up to L1C level, the L2 degraded data set will be corrected in the next L2 reprocessing campaign.

5. LONG-TERM ANALYSIS

5.1 Calibration Analysis

The calibration parameters are under monitoring. During the reporting period, there have been two Warm-NIR calibrations events: on 06th and 20th of January 2016.

The NIR calibration events have been monitored and the noise injection levels of the NIR diodes are stable and inside the range defined in the routine calibration plan.

The evolution of the noise temperature of the reference noise diodes Tna and Tnr computed with processor baseline V62x since the beginning of the mission is shown from Figure 1 to Figure 4. The evolution of the temperature parameters, which are related to the internal diode stability, are stable in particular for the NIR CA which is the only one used for the level 1 data calibration. The small deviation in the NIR calibration on 3rd June 2015 was due to a Radio Frequency Interference (RFI) that has corrupted the measurement. This calibration should not be used for the scientific processing of the data.

Figure 5 and Figure 6 present the evolution of the NIR Observed BT since the beginning of the mission for the V620x baseline.

The seasonal evolution of the calibration parameters present in the previous processor baseline V5xx (see the previous monthly report for April 2015) had been largely mitigated by the new calibration algorithm which decouple the variation of the antenna losses and the drift of the reference diode. This approach allows to compensate each drift separately improving the diode stability monitoring and increasing the accuracy of the consequent calibration correction. The impact on the final brightness temperature is a more stable long term measurement.

The leakage and cross-coupling factors of the NIR channels remain small and no problems can be observed apart from a peak in the phase of the NIR-AB cross-coupling term on 11 April 2012. That peak corresponds to an anomaly in the NIR-AB that did not have impact on the data.



Figure 1 Tna evolution of NIR AB (blue), NIR BC (green) and NIR CA (red) in the H-channel since the beginning of the mission. Thresholds in dashed lines





Figure 2 Tna evolution of NIR AB (blue), NIR BC (green) and NIR CA (red) in the V-channel since the beginning of the mission. Thresholds in dashed lines








Figure 4 Tnr evolution of NIR AB (blue), NIR BC (green) and NIR CA (red) in the V-channel since the beginning of the mission. Thresholds in dashed lines






Figure 5 NIR Observed BT evolution of NIR AB (blue), NIR BC (green) and NIR CA (red) in the H-channel since the beginning of the mission. Thresholds in dashed lines




Figure 6 NIR Observed BT evolution of NIR AB (blue), NIR BC (green) and NIR CA (red) in the V-channel since the beginning of the mission. Thresholds in dashed lines






Figure 7 Cross-coupling evolution in amplitude and phase of NIR AB (blue), NIR BC (green) and NIR CA (red) since the beginning of the mission





Figure 8 Leakage factor evolution in amplitude and phase of NIR AB (blue), NIR BC (green) and NIR CA (red) since the beginning of the mission





The LICEF calibration status is updated by long (every 8 weeks) and short (weekly) on-board calibration activities. No long calibration has been executed during the reporting period.

LICEF PMS gain is derived during the long calibration activity and the Figure 9 to Figure 20 show the evolution (V62x algorithm baseline) of the deviations of the PMS gain with respect to its average over time. Apart from antenna LCF_A_18, LCF_C_11, LCF_C_19, which had shown an evolution from the main trend (see Figure 12, 19, 20) the others PMS are stable.

Figure 21 to Figure 32 show the evolution of the PMS offsets (V62x algorithm baseline) derived during the short calibration activity.

Figure 33 shows the evolution of the average over all the baselines of the Fringe Washing Function (FWF) amplitude in the origin derived during the long calibration. The amplitude of the FWF at the origin does not show any drift and their values are inside the ranges defined in the routine calibration plan.




Figure 9 Evolution of the Δ PMS Gain of the LICEFS in CMN H1






Figure 11 Evolution of the Δ PMS Gain of the LICEFS in CMN A2




Figure 12 Evolution of the Δ PMS Gain of the LICEFS in CMN A3





Figure 13 Evolution of the Δ PMS Gain of the LICEFS in CMN H2










Figure 15 Evolution of the Δ PMS Gain of the LICEFS in CMN B2




Figure 16 Evolution of the Δ PMS Gain of the LICEFS in CMN B3




Figure 17 Evolution of the Δ PMS Gain of the LICEFS in CMN H3




Figure 18 Evolution of the Δ PMS Gain of the LICEFS in CMN C1





Figure 19 Evolution of the Δ PMS Gain of the LICEFS in CMN C2










Figure 21 Evolution of the Δ PMS Offset of the LICEFS in CMN H1




Figure 22 Evolution of the Δ PMS Offset of the LICEFS in CMN A1




Figure 23 Evolution of the Δ PMS Offset of the LICEFS in CMN A2




Figure 24 Evolution of the Δ PMS Offset of the LICEFS in CMN A3




Figure 25 Evolution of the Δ PMS Offset of the LICEFS in CMN H2






Figure 26 Evolution of the Δ PMS Offset of the LICEFS in CMN B1




Figure 27 Evolution of the Δ PMS Offset of the LICEFS in CMN B2




Figure 28 Evolution of the Δ PMS Offset of the LICEFS in CMN B3






Figure 29 Evolution of the Δ PMS Offset of the LICEFS in CMN H3




Figure 30 Evolution of the Δ PMS Offset of the LICEFS in CMN C1




Figure 31 Evolution of the Δ PMS Offset of the LICEFS in CMN C2




Figure 32 Evolution of the Δ PMS Offset of the LICEFS in CMN C3





Figure 33 Evolution of the average of the FWF Amplitude at the origin



The evolution of the average of the correlator offsets does not show any significant drift. Also, the correlation offsets between receivers that do not share local oscillator remains much smaller than the correlation offsets between receivers sharing local oscillator. This result is expected since any residual correlated signal arriving to a pair of receivers, arrives through the local oscillator signal.




Figure 34 Evolution of the average of the Correlator offsets for the baselines which share local oscillator




Figure 35 Evolution of the average of the Correlator offsets for the baselines which do not share local oscillator



5.2 Brightness Temperatures Trends over Dome-C Point (Antarctic)

The result of the monitoring of the evolution of the SMOS brightness temperature over Dome-C is shown in the Figure 36 (X and Y polarization at antenna frame for all the incidence angles) and in Figure 37, Figure 38 (H and V polarization at surface level for 42.0 degrees incidence angle for different areas of the Field Of View). The values are averaged every 18 days to reduce the noise and the value for July 2010 is subtracted and used as relative reference.

The evolution of the brightness temperature trend over Dome-C does not show any significant drift except for the beginning of 2015 in H polarization. This drift was due to a change on surface geophysical condition: accumulation of snow since November 2014 and rapidly evolution of snow density on 22 March 2015 when a strong wind has changed the surface condition. This event has impacted the emissivity of the ice that was confirmed by on-site L-band measurement (Dome-x experiment) and from the Aquarius data set.

The H polarization values were back to nominal from April 2015 onwards.






Figure 36: Dome-C X and Y polarization trends (all incidence angles)





IDEAS+-VEG-OQC-REP-2497 Issue 1.0

Figure 38: Dome-C H and V polarization trends in Extended Alias Free zone (incidence angle 42°)





6. PRODUCT QUALITY ANALYSIS

Level 1 data quality for January has found to be nominal except in the time intervals listed in the section 4.5. Weekly maps for ascending and descending passes for the Stokes 1, Stokes 3 and Stokes 4 in videos format can be found at:

https://earth.esa.int/web/guest/missions/esa-operational-eo-missions/smos/content/-/asset_publisher/t5Py/content/data-quality-7059

All the artificial patterns in the maps can be explained by the presence of RFIs.

Level 2 Soil Moisture data quality for January has found to be nominal. Weekly maps for ascending and descending passes for the soil moisture in videos format can be found at:

https://earth.esa.int/web/guest/missions/esa-operational-eo-missions/smos/content/-/asset_publisher/t5Py/content/data-quality-7059

The L2 Sea Surface Salinity data quality is nominal in the reporting period. Weekly maps for ascending and descending passes for good retrieved sea surface salinity in videos format can be found at:

https://earth.esa.int/web/guest/missions/esa-operational-eo-missions/smos/content/asset_publisher/t5Py/content/data-quality-7059

The lack of good retrieval at descending passes during the winter season is due to thermal effect on the instrument. In the winter season there is a stronger temperature gradient in the antennae surface that is only partially taken into account in the current calibration schema. As result the brightness temperature are somehow degraded for ocean application. This calibration issue is under investigation by the calibration team. For more details on soil moisture and sea surface salinity retrieval algorithms and caveats in data usage see the L2 Algorithm Theoretical Baseline Documents and the read-me-first note available here:

https://earth.esa.int/web/guest/missions/esa-operational-eo-missions/smos/content/-/asset_publisher/t5Py/content/data-processors-7632

7. ADF CONFIGURATION AT THE END OF THE REPORTING PERIOD

ADF File Type	Operational ADF Version (DPGS Baseline)	Updated
AUX APDL	SM_OPER_AUX_APDL	No
AUX APDNRT	SM OPER AUX APDNRT 20050101T000000 20500101T000000 207 001 6.EEF	No
AUX APDS	SM_OPER_AUX_APDS	No
AUX_ATMOS_	SM_OPER_AUX_ATMOS20050101T000000_20500101T000000_001_010_3.EEF	No
AUX BFP	SM_OPER_AUX_BFP20050101T000000_20500101T000000_340_004_3.EEF	No
AUX BNDLST	SM OPER AUX BNDLST 20050101T000000 20500101T000000 300 001 3	No
AUX BSCAT	SM_OPER_AUX_BSCAT20050101T000000_20500101T000000_300_003_3	No
AUX BULL B	SM_OPER_AUX_BULL_B_20151102T000000_20500101T000000_120_001_3	Yes
AUX_BWGHT_	SM_OPER_AUX_BWGHT20050101T000000_20500101T000000_340_006_3.EEF	No
AUX CNFFAR	SM_OPER_AUX_CNFFAR_20050101T000000_20500101T000000_100_002_3.EEF	No
AUX CNFL0P	SM OPER AUX CNFLOP 20050101T000000 20500101T000000 001 005 3.EEF	No
AUX CNFL1P	SM_OPER_AUX_CNFL1P_20110206T010100_20500101T000000_620_051_3.EEF	No
AUX_CNFNRT	SM_OPER_AUX_CNFNRT_20050101T000000_20500101T000000_620_010_3.EEF	No
AUX CNFOSD	SM_OPER_AUX_CNFOSD_20050101T000000_20500101T000000_001_024_3.EEF	No
AUX_CNFOSF	SM_OPER_AUX_CNFOSF_20050101T000000_20500101T000000_001_026_3.EEF	No
AUX_CNFSMD	SM_OPER_AUX_CNFSMD_20050101T000000_20500101T000000_001_014_3.EEF	No
AUX_CNFSMF	SM_OPER_AUX_CNFSMF_20050101T000000_20500101T000000_001_014_3.EEF	No
AUX_DFFFRA	SM_OPER_AUX_DFFFRA_20050101T000000_20500101T000000_001_005_3	No
AUX_DFFLMX	SM_OPER_AUX_DFFLMX_20050101T000000_20500101T000000_001_006_3	No
AUX_DFFSOI	SM_OPER_AUX_DFFSOI_20050101T000000_20500101T000000_001_002_3	No
AUX_DFFXYZ	SM_OPER_AUX_DFFXYZ_20050101T000000_20500101T000000_001_003_3	No
AUX_DGG	SM_OPER_AUX_DGG20050101T000000_20500101T000000_300_003_3	No
AUX_DGGXYZ	SM_OPER_AUX_DGGXYZ_20050101T000000_20500101T000000_001_004_3	No
AUX_DISTAN	SM_OPER_AUX_DISTAN_20050101T000000_20500101T000000_001_011_3	No
AUX_DTBCUR	SM_OPER_AUX_DTBCUR20120504T203936_20500101T000000_624_001_1Initialization file for the deployment of the L2OS V62x processor.	No
AUX_ECOLAI	SM_OPER_AUX_ECOLAI_20050101T000000_20500101T000000_305_006_3	No
AOX_LOOLAI	SM_OPER_AUX_ECMCDF_20101109T000000_20500101T000000_001_001_3.EEF	No
AUX_ECMCDF	SM_OPER_AUX_ECMCDF_20050101T000000_20101109T000000_001_002_3	NIa
AUX_FAIL	SM_OPER_AUX_FAIL20050101T000000_20500101T000000_300_004_3.EEF	No
AUX_FLTSEA	SM_OPER_AUX_FLTSEA_20050101T000000_20500101T000000_001_010_3.EEF	No
AUX_FOAM	SM_OPER_AUX_FOAM20050101T000000_20500101T000000_001_011_3	No
AUX_GAL_OS	SM_OPER_AUX_GAL_OS_20050101T000000_20500101T000000_001_011_3	No
AUX_GAL_SM	SM_OPER_AUX_GAL_SM_20050101T000000_20500101T000000_001_003_3	No No
AUX_GAL2OS	SM_OPER_AUX_GAL2OS_20050101T000000_20500101T000000_001_016_3	No
AUX_GALAXY	SM_OPER_AUX_GALAXY_20050101T000000_20500101T000000_300_004_3	No
AUX_GALNIR	SM_OPER_AUX_GALNIR_20050101T000000_20500101T000000_300_003_3	No
AUX_LANDCL	SM_OPER_AUX_LANDCL_20050101T000000_20500101T000000_001_004_3.EEF	No
AUX_LCF	SM_OPER_AUX_LCF20050101T000000_20500101T000000_500_016_3.EEF	No No
AUX_LSMASK	SM_OPER_AUX_LSMASK_20050101T000000_20500101T000000_300_003_3 SM_OPER_AUX_MASK20050101T000000_20500101T000000_300_002_3	No
AUX_MASK		No
AUX_MISP	SM_OPER_AUX_MISP20050101T000000_20500101T000000_300_004_3.EEF	No
AUX_MN_WEF	SM_OPER_AUX_MN_WEF_20050101T000000_20500101T000000_001_002_3	No
AUX_MOONT_	SM_OPER_AUX_MOONT20050101T000000_20500101T000000_300_002_3 SM_OPER_AUX_N25620050101T000000_20500101T000000_504_002_3	No
AUX_N256	SM_OPER_AUX_NIR20050101T000000_20500101T000000_504_002_3 SM_OPER_AUX_NIR20050101T000000_20500101T000000_500_010_3.EEF	No
AUX_NIR	3 V _O LN_NON_ V N200301011000000_203001011000000_300_010_3.EEF	INU



AUX_NRTMSK	SM_OPER_AUX_NRTMSK_20050101T000000_20500101T000000_207_001_6	No
AUX_OTT1D_	SM_OPER_AUX_OTT1D20120504T203936_20500101T000000_624_001_1 Initialization file for the deployment of the L2OS V62x processor. Since level 2 OS processor V62x the new file is generated on routine basis by the level 2 post processor	No
AUX_OTT1F_	SM_OPER_AUX_OTT1F20120504T203936_20500101T000000_624_001_1 Initialization file for the deployment of the L2OS V62x processor. Since level 2 OS processor V62x the new file is generated on routine basis by the level 2 post processor	No
AUX_OTT2D_	SM_OPER_AUX_OTT2D20120504T203936_20500101T000000_624_001_1 Initialization file for the deployment of the L2OS V62x processor. Since level 2 OS processor V62x the new file is generated on routine basis by the level 2 post processor	No
AUX_OTT2F_	SM_OPER_AUX_OTT2F20120504T203936_20500101T000000_624_001_1 Initialization file for the deployment of the L2OS V62x processor. Since level 2 OS processor V62x the new file is generated on routine basis by the level 2 post processor	No
AUX_OTT3D_	SM_OPER_AUX_OTT3D20120504T203936_20500101T000000_624_001_1 Initialization file for the deployment of the L2OS V62x processor. Since level 2 OS processor V62x the new file is generated on routine basis by the level 2 post processor	No
AUX_OTT3F_	SM_OPER_AUX_OTT3F20120504T203936_20500101T000000_624_001_1 Initialization file for the deployment of the L2OS V62x processor. Since level 2 OS processor V62x the new file is generated on routine basis by the level 2 post processor	No
AUX_PATT	SM_OPER_AUX_PATT20050101T000000_20500101T000000_320_003_3	No
AUX_PLM	SM_OPER_AUX_PLM20050101T000000_20500101T000000_600_008_3.EEF	No
AUX_PMS	SM_OPER_AUX_PMS20050101T000000_20500101T000000_600_011_3.EEF	No
AUX_RFI	SM_OPER_AUX_RFI20050101T000000_20500101T000000_300_003_3	No
AUX_RFILST	Since level 1 processor version V62x the file is generated by CATDS on monthly basis	No
AUX_RGHNS1	SM_OPER_AUX_RGHNS1_20050101T000000_20500101T000000_001_015_3	No
AUX_RGHNS2	SM_OPER_AUX_RGHNS2_20050101T000000_20500101T000000_001_013_3	No
AUX_RGHNS3	SM_OPER_AUX_RGHNS3_20050101T000000_20500101T000000_001_015_3.EEF	No
AUX_SGLINT	SM_OPER_AUX_SGLINT_20050101T000000_20500101T000000_001_011_3	No
AUX_SOIL_P	File discontinued since level 2 SM processor V62x SM_OPER_AUX_SOIL_P_20050101T000000_20500101T000000_001_002_3	No
AUX_SPAR	SM_OPER_AUX_SPAR20110112T091500_20500101T000000_340_012_3.EEF SM_OPER_AUX_SPAR20100111T120700_20110112T091500_340_011_3.EEF SM_OPER_AUX_SPAR20050101T000000_20100111T120700_340_010_3.EEF	No
AUX_SSS	SM_OPER_AUX_SSS20050101T000000_20500101T000000_001_013_3	No
AUX_SUNT	SM_OPER_AUX_SUNT20050101T000000_20500101T000000_300_002_3	No
AUX_WEF	SM_OPER_AUX_WEF20050101T000000_20500101T000000_001_003_3	No
MPL_ORBSCT	SM_OPER_MPL_ORBSCT_20091102T031142_20500101T000000_360_001_1	No

APPENDIX A. CONFIGURATION DOCUMENT LIST

The list of internal documents used for the generation of this report is:

- Unavailability.xls
- Details_Calibrations.xls
- SMOS-CEC-VEG-IPF-REP-0609_v1.76_SMOS_Auxiliary_Data_File_List.pdf



This Page Is Intentionally Blank



End of Document